



current/voltage measuring module for dry-running protection of centrifugal pumps in hazardous areas, current setting 3...40 A, voltage measurement up to 690 V, width 45 mm, straight-through transformer

|                                                                                 |                                                                                                                                                                                                                                                                                                          |
|---------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| product brand name                                                              | SIRIUS                                                                                                                                                                                                                                                                                                   |
| product designation                                                             | Current/voltage measuring module                                                                                                                                                                                                                                                                         |
| <b>General technical data</b>                                                   |                                                                                                                                                                                                                                                                                                          |
| measuring procedure                                                             | RMS value measurement                                                                                                                                                                                                                                                                                    |
| size of the circuit-breaker                                                     | S00, S0                                                                                                                                                                                                                                                                                                  |
| product function                                                                | <ul style="list-style-type: none"> <li>• current measurement</li> <li>• voltage measurement</li> <li>• active power measurement</li> <li>• energy measurement</li> <li>• frequency measurement</li> <li>• active power monitoring for pump dry-run according to Ignition protection type Ex b</li> </ul> |
| measuring procedure for current measurement                                     | TRMS                                                                                                                                                                                                                                                                                                     |
| current measuring range extension with external current transformers            | Yes                                                                                                                                                                                                                                                                                                      |
| measuring procedure for voltage measurement                                     | TRMS                                                                                                                                                                                                                                                                                                     |
| measurable supply voltage between the line conductors at AC maximum rated value | 690 V                                                                                                                                                                                                                                                                                                    |
| product component                                                               | <ul style="list-style-type: none"> <li>• input for thermistor connection</li> </ul>                                                                                                                                                                                                                      |
| consumed active power                                                           | 0.5 W                                                                                                                                                                                                                                                                                                    |
| insulation voltage                                                              | <ul style="list-style-type: none"> <li>• with degree of pollution 3 at AC rated value</li> <li>• for wires of main circuit according to IEC 60947-1 rated value</li> </ul>                                                                                                                               |
| surge voltage resistance rated value                                            | 6 000 V                                                                                                                                                                                                                                                                                                  |
| shock resistance according to IEC 60068-2-27                                    | 15g / 11 ms; with basic unit snapped on                                                                                                                                                                                                                                                                  |
| vibration resistance                                                            | 1-6 Hz / 15 mm; 6-500 Hz / 2 g; with basic unit snapped on: 1g                                                                                                                                                                                                                                           |
| Substance Prohibitance (Date)                                                   | 05/28/2009                                                                                                                                                                                                                                                                                               |
| SVHC substance name                                                             | Lead - 7439-92-1<br>Lead monoxide (lead oxide) - 1317-36-8<br>2-methyl-1-(4-methylthiophenyl)-2-morpholinopropan-1-one - 71868-10-5                                                                                                                                                                      |
| Weight                                                                          | 0.198 kg                                                                                                                                                                                                                                                                                                 |
| <b>Electromagnetic compatibility</b>                                            |                                                                                                                                                                                                                                                                                                          |
| EMC emitted interference according to IEC 60947-1                               | class A                                                                                                                                                                                                                                                                                                  |
| EMC immunity according to IEC 60947-1                                           | corresponds to degree of severity 3                                                                                                                                                                                                                                                                      |
| conducted interference                                                          | <ul style="list-style-type: none"> <li>• due to burst according to IEC 61000-4-4</li> <li>• due to conductor-earth surge according to IEC 61000-4-5</li> <li>• due to conductor-conductor surge according to IEC 61000-4-5</li> </ul>                                                                    |

|                                                                                    |                                                                                                                                                |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------|
| field-based interference according to IEC 61000-4-3                                | 10 V/m                                                                                                                                         |
| <b>Inputs/ Outputs</b>                                                             |                                                                                                                                                |
| number of outputs as contact-affected switching element                            | 0                                                                                                                                              |
| <b>Protective and monitoring functions</b>                                         |                                                                                                                                                |
| product function                                                                   |                                                                                                                                                |
| • power factor monitoring                                                          | Yes                                                                                                                                            |
| • ground-fault monitoring                                                          | Yes                                                                                                                                            |
| • voltage detection                                                                | Yes                                                                                                                                            |
| trip class                                                                         | CLASS 5E                                                                                                                                       |
| product function                                                                   |                                                                                                                                                |
| • current detection                                                                | Yes                                                                                                                                            |
| • overload protection                                                              | Yes                                                                                                                                            |
| <b>Precision</b>                                                                   |                                                                                                                                                |
| measuring precision                                                                |                                                                                                                                                |
| • of frequency measurement                                                         | +/- 1.5 %, 2.25 A ... 80 A, 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), cos phi (0.5...1), 50/60 Hz, 25 °C                           |
| • for current measurement 1                                                        | +/- 1.5 %, in range 2.25 A ... 80 A, in range 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), 50/60 Hz, 25 °C                            |
| • for current measurement 2                                                        | +/- 3%, in range 80 A ... 320 A, in range 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), 50/60 Hz, 25 °C                                |
| • for voltage measurement 1                                                        | +/- 1.5 %, in range 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), 50/60 Hz, 25 °C                                                      |
| • at cos phi-measurement 1                                                         | +/- 1.5 %, 7.5 A ... 230 A, 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), cos phi (0.5...1), 50/60 Hz, 25 °C                           |
| • at cos phi-measurement 2                                                         | +/- 5%, 80 A ... 320 A, 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), cos-phi (0.5...1), 50/60 Hz, 25 °C                               |
| • at active power measurement 1                                                    | +/- 5%, 7.5 A ... 230 A, 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), cos-phi (0.5...1), 50/60 Hz, 25 °C                              |
| • at active power measurement 2                                                    | +/- 10%, 80 A ... 320 A, 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), cos-phi (0.5...1), 50/60 Hz, 25 °C                              |
| • at energy measurement 1                                                          | +/- 5%, 2.25 A ... 80 A, 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), cos-phi (0.5...1), 50/60 Hz, 25 °C                              |
| • at energy measurement 2                                                          | +/- 10%, 80 A ... 320 A, 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), cos-phi (0.5...1), 50/60 Hz, 25 °C                              |
| • at apparent power measurement 1                                                  | +/- 3%, 2.25 A ... 80 A, 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), cos-phi (0.5...1), 50/60 Hz, 25 °C                              |
| • at apparent power measurement 2                                                  | +/- 5 %, 80 A ... 320 A, 0.85 x 110 V ... 1.1 x 690 V (line-to-line voltages), cos phi (0.5...1), 50/60 Hz, 25 °C                              |
| accuracy of ground-fault monitoring                                                | In the range 30 % .. 120 %/Is: +/- 10 % (Class CI-A), in range 15 % .. 30 % Ie: +/- 25 % (Class CI-B), both values acc. to IEC 60947-1 Annex T |
| temperature drift per °C                                                           | 0.01 %/°C; Reference temperature: 25°C                                                                                                         |
| measured variable frequency                                                        | 45 ... 65 Hz                                                                                                                                   |
| <b>Installation/ mounting/ dimensions</b>                                          |                                                                                                                                                |
| mounting position                                                                  | any                                                                                                                                            |
| fastening method                                                                   | screw and snap-on mounting                                                                                                                     |
| height                                                                             | 84 mm                                                                                                                                          |
| width                                                                              | 45 mm                                                                                                                                          |
| depth                                                                              | 64 mm                                                                                                                                          |
| required spacing                                                                   |                                                                                                                                                |
| • top                                                                              | 30 mm                                                                                                                                          |
| • bottom                                                                           | 30 mm                                                                                                                                          |
| • left                                                                             | 0 mm                                                                                                                                           |
| • right                                                                            | 0 mm                                                                                                                                           |
| diameter of inlet opening                                                          | 7.5 mm                                                                                                                                         |
| diameter of inlet opening for current measurement                                  | 7.5 mm                                                                                                                                         |
| <b>Connections/ Terminals</b>                                                      |                                                                                                                                                |
| type of electrical connection                                                      |                                                                                                                                                |
| • for main current circuit                                                         | straight-through transformers                                                                                                                  |
| • for auxiliary and control circuit                                                | screw-type terminals                                                                                                                           |
| type of electrical connection at the measurement inputs for voltage                | screw-type terminals                                                                                                                           |
| type of connectable conductor cross-sections at the measurement inputs for voltage |                                                                                                                                                |
| • finely stranded with core end processing                                         | 1x (0.25 ... 2.5 mm²), 2x (0.25 ... 1.0 mm²)                                                                                                   |
| • solid                                                                            | 1x (0.25 ... 2.5 mm²), 2x (0.25 ... 1.0 mm²)                                                                                                   |

|                                                                                                             |                                                                  |
|-------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>• for AWG cables solid</li> <li>• for AWG cables stranded</li> </ul> | 1x (24 ... 14), 2x (24 ... 18)<br>1x (20 ... 14), 2x (20 ... 16) |
| <b>tightening torque at the measurement inputs for voltage</b>                                              | 0.5 ... 0.6 N·m                                                  |
| <b>tightening torque [lbf·in] at the measurement inputs for voltage</b>                                     | 4.4 ... 5.3 lbf·in                                               |

#### Ambient conditions

|                                                                                                                                                                                                                               |                                                                                                                                                                                                                                                                                             |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>installation altitude at height above sea level</b> <ul style="list-style-type: none"> <li>• 1 maximum</li> <li>• 2 maximum</li> <li>• 3 maximum</li> </ul>                                                                | 2 000 m<br>3 000 m; max. +50 °C (no protective separation)<br>4 000 m; max. +40 °C (no protective separation)                                                                                                                                                                               |
| <b>ambient temperature</b> <ul style="list-style-type: none"> <li>• during operation</li> <li>• during storage</li> <li>• during transport</li> </ul>                                                                         | -25 ... +60 °C<br>-40 ... +80 °C<br>-40 ... +80 °C                                                                                                                                                                                                                                          |
| <b>environmental category</b> <ul style="list-style-type: none"> <li>• during operation according to IEC 60721</li> <li>• during storage according to IEC 60721</li> <li>• during transport according to IEC 60721</li> </ul> | 3K6 (no formation of ice, no condensation, relative humidity 10 ... 95%), 3C3 (no salt mist), 3S2 (sand must not get into the devices), 3M6<br>1K6 (no condensation, relative humidity 10 ... 95%), 1C2 (no salt mist), 1S2 (sand must not get into the devices), 1M4<br>2K2, 2C1, 2S1, 2M2 |
| relative humidity during operation                                                                                                                                                                                            | 10 ... 95 %                                                                                                                                                                                                                                                                                 |

#### Short-circuit protection

|                                                  |    |
|--------------------------------------------------|----|
| <b>product function short circuit protection</b> | No |
|--------------------------------------------------|----|

#### ATEX

|                                                                                                                                                                            |                                                                                                  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------|
| <b>certificate of suitability</b> <ul style="list-style-type: none"> <li>• IECEx</li> <li>• according to ATEX directive 2014/34/EU</li> <li>• according to UKCA</li> </ul> | Yes; IECEx PTB 18.0004X<br>BVS 06 ATEX F001, PTB 18 ATEX 5003 X<br>ITS21UKEX0464, ITS21UKEX0455X |
| explosion device group and category according to ATEX directive 2014/34/EU                                                                                                 | II (2) G, II (2) D, I (M2) / I (1G/M2), II (1/2) G, II (1G/2D)                                   |

#### Galvanic isolation

|                                                                      |                                                                                                                                                                                                        |
|----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>(electrically) protective separation according to IEC 60947-1</b> | All circuits with protective separation (double creepage paths and clearances), the information in the "Protective Separation" test report, No. A0258, must be observed (link see further information) |
|----------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

#### Main circuit

|                                                                                                                                                                                              |                                |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|
| <b>number of poles for main current circuit</b>                                                                                                                                              | 3                              |
| <b>adjustable current response value current of the current-dependent overload release</b>                                                                                                   | 3 ... 40 A                     |
| <b>operating voltage</b> <ul style="list-style-type: none"> <li>• at AC <ul style="list-style-type: none"> <li>— at 50 Hz rated value</li> <li>— at 60 Hz rated value</li> </ul> </li> </ul> | 110 ... 690 V<br>110 ... 690 V |
| <b>operating frequency rated value</b>                                                                                                                                                       | 50 ... 60 Hz                   |

#### Control circuit/ Control

|                               |                            |
|-------------------------------|----------------------------|
| <b>type of voltage</b>        | AC                         |
| <b>inrush current maximum</b> | 400 A; 10 x I <sub>o</sub> |

#### Approvals Certificates

|                          |     |
|--------------------------|-----|
| General Product Approval | EMV |
|--------------------------|-----|



|     |                                |
|-----|--------------------------------|
| EMV | For use in hazardous locations |
|-----|--------------------------------|

[KC](#)



[Miscellaneous](#)

|                   |                      |
|-------------------|----------------------|
| Test Certificates | Maritime application |
|-------------------|----------------------|

[Type Test Certificates/Test Report](#)

[Special Test Certificate](#)

[Special Test Certificate](#)



|                      |       |             |                          |
|----------------------|-------|-------------|--------------------------|
| Maritime application | other | Environment | Industrial Communication |
|----------------------|-------|-------------|--------------------------|



[Confirmation](#)



[Environmental Confirmations](#)



#### Further information

##### Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

##### Information for data generation and storage

<https://support.industry.siemens.com/cs/ww/en/view/109995012>

##### Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

##### Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7121-1AA01-0>

##### Cax online generator


<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7121-1AA01-0>


##### Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF7121-1AA01-0>

##### Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3UF7121-1AA01-0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3UF7121-1AA01-0&lang=en)





last modified:

4/2/2025 