

Addressing plug, for assigning the PROFIBUS address to SIMOCODE pro without PC/PG



General technical data

product brand name	SIRIUS
product designation	addressing plug
design of the product	For assigning the PROFIBUS or Modbus RTU address without using a PC/PG
ambient temperature	
• during storage	-40 ... +80 °C
• during operation	-25 ... +60 °C
• during transport	-40 ... +80 °C

Certificates/ approvals

General Product Approval



EG-Konf.



CCC

[Confirmation](#)



UL



EMV Test Certificates Marine / Shipping



RCM

[KC](#)

[Type Test Certificates/Test Report](#)



ABS



DNV



LRS

Marine / Shipping other Environment Industrial Communication



RMRS

[Confirmation](#)

[Environmental Confirmations](#)



Profibus

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3UF7910-0AA00-0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3UF7910-0AA00-0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3UF7910-0AA00-0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)



