




wire connector TA2.3 2 x 4 AWG...300 kcmil with control wire tap; for 2 cables; 3 units; incl. terminal cover extended with holes for voltage testing; accessory for: 3VA61/62 plug-in socket/withdrawable socket 3VA61/62

Model		
product brand name	SETRON	
product designation	Circular conductor terminal 2 cables 3 units	
accessories	Wire connector	
General technical data		
designation / of the terminal	TA2.3	
type of electrical connection / with control wire tap	Yes	
Connections according IEC		
connectable conductor cross-section	- for copper cable / stranded / minimum25 mm² - for copper cable / stranded / maximum150 mm² - for aluminum cable / stranded / minimum25 mm² - for aluminum cable / stranded / maximum150 mm²	
stripped length	26 / 51 mm	
tightening torque / when using copper cables	- stranded25 - 150 mm²: 31.1 Nm - finely stranded25 - 150 mm²: 31.1 Nm - finely stranded / with core end processing25 - 70 mm²: 31.1 Nm	
Connetctions according UL		
permissible temperature / of connectable conductor / according to UL 486A-486B	75 °C	
stripped length	1.0 / 2.0 in	
connectable conductor cross-section	- for copper cable / stranded / minimum4 AWG - for copper cable / stranded / maximum300 kcmil - for aluminum cable / stranded / minimum4 AWG - for aluminum cable / stranded / maximum300 kcmil	
tightening torque / when using copper cables	stranded4 AWG - 300 kcmil: 275 lb-in	
Certificates		
General Product Approval	EMV	Maritime application
 EG-Konf.		Miscellaneous
		 RCM
		 LRS
other	Environment	

Further information**Information on the packaging**<https://support.industry.siemens.com/cs/ww/en/view/109813875>**Information for data generation and storage**<https://support.industry.siemens.com/cs/ww/en/view/109995012>**Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9243-0JC28>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/3VA9243-0JC28>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9243-0JC28**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>

last modified:

8/8/2025

