



operator kit with Bowden cable Max-Flex operator Bowden cable, single length 1.2 m (48") accessory for: 3VA51/52; 3VA61/62 only for the UL market only for UL applications not approved for IEC

| Model                    |                           |
|--------------------------|---------------------------|
| product brand name       | SETRON                    |
| product designation      | Bowden wire actuator      |
| accessories              | Bowden cable for Max-Flex |
| Mechanical Design        |                           |
| depth                    | 1 200 mm                  |
| Certificates             |                           |
| General Product Approval |                           |



[Miscellaneous](#)



| EMV                                                                                        | Maritime application                                                                       | other                        | Environment                   |                                             |                                             |
|--------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------|------------------------------|-------------------------------|---------------------------------------------|---------------------------------------------|
| <br>RCM | <br>LRS | <a href="#">Confirmation</a> | <a href="#">Miscellaneous</a> | <a href="#">Environmental Confirmations</a> | <a href="#">Environmental Confirmations</a> |

| Further information                                                                                                                                                                                                                                              |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Information on the packaging<br><a href="https://support.industry.siemens.com/cs/ww/en/view/109813875">https://support.industry.siemens.com/cs/ww/en/view/109813875</a>                                                                                          |
| Information- and Downloadcenter (Catalogs, Brochures,...)<br><a href="http://www.siemens.com/lowvoltage/catalogs">http://www.siemens.com/lowvoltage/catalogs</a>                                                                                                 |
| Industry Mall (Online ordering system)<br><a href="https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9278-0CC20">https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9278-0CC20</a>                                          |
| Service&Support (Manuals, Certificates, Characteristics, FAQs,...)<br><a href="https://support.industry.siemens.com/cs/ww/en/ps/3VA9278-0CC20">https://support.industry.siemens.com/cs/ww/en/ps/3VA9278-0CC20</a>                                                |
| Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)<br><a href="http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9278-0CC20">http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3VA9278-0CC20</a> |
| CAX-Online-Generator<br><a href="http://www.siemens.com/cax">http://www.siemens.com/cax</a>                                                                                                                                                                      |
| Tender specifications<br><a href="http://www.siemens.com/specifications">http://www.siemens.com/specifications</a>                                                                                                                                               |



---

last modified:

5/26/2025 

