



circular conduc. terminal TA2.8 1x250...750 kcmil; 2x250 kcmil for 1 cable 250 - 750 kcmil or 2 cables 250 kcmil; with auxiliary conductor voltage tap 3 units accessory for: 3VA53/54; 3VA63/64 up to 400 A

Model	
product brand name	SETRON
product designation	circular conductor terminal
accessories	Wire connector
General technical data	
designation / of the terminal	TA2.8
type of electrical connection / with control wire tap	Yes
Connections according IEC	
stripped length	38,1 mm
Connections according UL	
permissible temperature / of connectable conductor / according to UL 486A-486B	90 °C
stripped length	1.5 in
connectable conductor cross-section	
• for copper cable / stranded / minimum	250 kcmil
• for copper cable / stranded / maximum	750 kcmil
• for aluminum cable / stranded / minimum	250 kcmil
• for aluminum cable / stranded / maximum	750 kcmil
Certificates	
General Product Approval	EMV
	Marine / Shipping




[Miscellaneous](#)



other	Environment
Confirmation	Environmental Con-
Miscellaneous	firmations
Miscellaneous	Environmental Con-
	firmations

Further information

Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
 Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
 Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3VA9373-0JC24>
 Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3VA9373-0JC24>



last modified:

11/27/2024 

