SIEMENS

Figure similar

line reactor for frequency converter; phases: 3; Un1(V): 500; Ithmax 1(A) / F1(Hz): 5 /50; I LN (A): 4.5; UK(%): 2; LN(MH): 3.68; temperature rise/insulation class: 40 /B; IP00; connection: screw/flat-type connection; EN 61558-2-20 >UL/CSA-recognized< >reactor<

General technical data

product designation		Netzdrossel f. FU
phase number		3
type of voltage		AC
operating voltage rated value	V	500
operating frequency rated value	Hz	50
•		
— operational current at AC rated value	A	4.5
— current at AC maximum	A	5
inductivity rated value	H	0.0037
relative inductive drop in voltage for rated value of the current, voltage and frequency	%	2
power loss [W] of the coil	W	11.5
power loss [W] of the iron core	W	5.6

Mechanical data

type of electrical connection for main current circuit		screw-type terminals / tab terminals
width	m	0.088
height	m	0.108
depth	m	0.057

Ambient conditions

thermal class according to IEC 60085		B
ambient temperature rated value	°C	40
protection class IP		IP00

Certificates/ approvals

General Product Approval	other	Environment
CE EG-Konf.	Confirmation	Environmental Confirmations
UKCA		
EAC		
产品合格 QC PASS		

Further information

Information on the packaging
https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage
https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,…)
https://www.siemens.com/ic10
Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=4EP3200-2US00

Cax online generator
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=4EP3200-2US00
Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
https://support.industry.siemens.com/cs/ww/en/ps/4EP3200-2US00
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=4EP3200-2US00&lang=en

last modified: 4/8/2025 ⬈