

Data sheet

US2:52SX2GABJ2K1

Selector switch, metal, NEMA 4X Maintained Short lever, G Cam 1NC + 1NO left, 1NC right 3 position Complete device white insert Non-illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Enclosure

number of command points	1
delivery state as a kit	No

Actuator

material of the actuating element	plastic
number of contact modules	3
type of unlocking device	rotate-to-unlatch mechanism
number of switching positions	3

Front ring

product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	black

General technical data

product function positive opening	Yes
product component	
● light source	No
insulation voltage rated value	600 V
protection class IP	IP66
operating frequency maximum	600 1/h
thermal current	10 A
Weight	0.23 kg

Auxiliary circuit

number of NC contacts for auxiliary contacts	2
number of NO contacts for auxiliary contacts	1
operational current at AC-15	
● at 110 V rated value	60 A
● at 230 V rated value	30 A
● at 400 V rated value	15 A
● at 500 V rated value	12 A

Connections/ Terminals

type of electrical connection	screw terminal
tightening torque of the screws in the bracket maximum	20 N·m
tightening torque [lbf-in] with screw-type terminals	8 lbf-in

Ambient conditions

ambient temperature	
● during operation	-35 ... +70 °C
● during storage	-40 ... +85 °C

Installation/ mounting/ dimensions

shape of the installation opening	round
-----------------------------------	-------

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SX2GABJ2K1>

Cax online generator

<http://support.automation.siemens.com/WW/CAOrder/default.aspx?lang=en&mlfb=US2:52SX2GABJ2K1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SX2GABJ2K1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SX2GABJ2K1&lang=en

last modified:

4/8/2024 