

DIAZED fuse link 500 V Slow-response, TNDZ, E16, 2A



Figure similar

Model			
product brand name		SETRON	
product designation		DIAZED fuse	
design of the product		For cable and line protection	
design of the fuse link		DIAZED fuse link	
General technical data			
tripping characteristic class		time-lag (T)	
size of fuse system according to EN 60269-1		NDz	
operating class of the fuse link		gG	
Supply voltage			
supply voltage			
• at AC		500 V	
• at DC		500 V	
Protection class			
protection class IP		IP20, with connected conductors	
Breaking Capacity			
switching capacity current			
• at AC according to IEC 60947-2 rated value		40 kA	
• at DC according to IEC 60947-2 rated value		1.6 kA	
Dissipation			
power loss [W]		0.85 W	
power loss [W] for rated value of the current at AC in hot operating state per pole		0.85 W	
Appearance			
color coding of the fuse link		pink	
Product details			
product description		Using screw adapter or adapter sleeves	
Mechanical Design			
mounting position		Any, preferably vertical	
Net Weight		12 g	
Environmental conditions			
ambient temperature during operation			
• minimum		-5 °C	
• maximum		40 °C	
environmental category		Up to 45°C at 95 % rel. humidity	
environmental category during storage		air humidity 90% at 20°C	
Approvals Certificates			
General Product Approval		other	Environment



[Environmental Con-
firmations](#)

Environment

[Environmental Con-
firmations](#)

Further information

Information on the packaging

<https://support.industry.siemens.com/cs/ww/en/view/109813875>

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SA211>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5SA211>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)


http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SA211

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



last modified:

4/11/2025

