




NEOZED fuse-link, D02, 50 A, gG, Un AC: 400 V, Un DC: 250 V, with silver-coated contact-caps

Figure similar

Model	
product brand name	SENTRON
product designation	NEOZED fuse link
design of the product	With silver-plated contact caps
product version	Pack of 10
design of the fuse link	NEOZED fuse link
General technical data	
size of fuse system according to EN 60269-1	D02
operating class of the fuse link	gG
Supply voltage	
supply voltage	
• at AC	400 V
• at DC	250 V
operating voltage rated value	400 V
protection class IP	IP20, with connected conductors
switching capacity current according to IEC 60947-2 rated value	50 kA
Dissipation	
power loss [W] for rated value of the current at AC in hot operating state per pole	3.1 W
Main circuit	
operational current rated value	50 A
Appearance	
color coding of the fuse link	White
maximum short-circuit current breaking capacity (I <sub>cu</sub> ) at AC rated value	50 kA
Mechanical Design	
mounting position	Any, preferably vertical
Net Weight	14 g
ambient temperature during operation	
• minimum	-25 °C
• maximum	40 °C
environmental category	Up to 45°C at 95 % rel. humidity
Approvals Certificates	
General Product Approval	other



[Confirmation](#)[Environmental Con-  
firmations](#)[Environmental Con-  
firmations](#)**Further information****Information on the packaging**<https://support.industry.siemens.com/cs/ww/en/view/109813875>**Information- and Downloadcenter (Catalogs, Brochures,...)**<http://www.siemens.com/lowvoltage/catalogs>**Industry Mall (Online ordering system)**<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2350>**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**<https://support.industry.siemens.com/cs/ww/en/ps/5SE2350>**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SE2350](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2350)**CAX-Online-Generator**<http://www.siemens.com/cax>**Tender specifications**<http://www.siemens.com/specifications>

last modified:

4/10/2025

