



Connecting terminal, 35 mm² according to UL 489, 480Y/277V for LS 5SJ4...-HG Infeed LS

Model	
product brand name	SETRON
product designation	Connecting terminal
design of the product	35 mm ² , acc. to UL 489, 480Y/277 V for MCBs 5SJ4...-HG infeed MCB
Supply voltage	
operating voltage at AC rated value	1 000 V
Connections	
tightening torque	
• minimum	4 N·m
• maximum	4 N·m
type of connectable conductor cross-sections for copper conductor stranded	2.5 - 35 mm ²
Mechanical Design	
height	31.1 mm
width	16.2 mm
depth	25.7 mm
length	74.7 mm
Net Weight	36 g
Approvals Certificates	
General Product Approval	other



[Miscellaneous](#)



other	Environment
Confirmation	Environmental Confirmations
	Environmental Confirmations

Further information
Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875
Information for data generation and storage https://support.industry.siemens.com/cs/ww/en/view/109995012
Information- and Downloadcenter (Catalogs, Brochures,...) http://www.siemens.com/lowvoltage/catalogs
Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5ST3666-0HG

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5ST3666-0HG>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5ST3666-0HG

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



