

SIMATIC IPC BX-59A (box PC); mainboard (chipset R680E); 4x Gigabit Ethernet (IE/PN) RJ45; 6x USB 3.1 Gen. 2; 1x USB-C, 2x serial (COM); 2x DP; audio; 2x SIM slots; 2xM.2 flex module slots internal; RAID controller onboard; watchdog,temperature/fan monitoring; Core i5-13500E, 65 W; 14C(6P+8E)/20T; 2.4(4.6) GHz; with 24 V DC, 400 W power supply 512 GB 2.5" SATA SSD 16 GB DDR5(1*16) without hardware extension (M.2) no power supply unit cable Windows 10 Enterprise LTSC 2021, 64-bit, MUI, for Core i5 (without USB-Stick restore image; D&D) no expansion module no expansion module, no EM memory

General information	
Product type designation	BX-59A
Installation type/mounting	
Mounting	Wall mounting, book mounting, desk mounting, tower mounting
Design	Box PC, built-in unit
Supply voltage	
Type of supply voltage	400 W / 24 V / 19.2 - 28.8 VDC; 220 W / 12-24 V / 9 - 36 VDC
Rated value (DC)	24 V; 12...24 V DC on 220 W
Mains buffering	
• Mains/voltage failure stored energy time	20 ms
Processor	
Processor type	Core i9-13900E 24C (8P+16E)/32T, 1.8 (5.2) GHz, 36 MB cache; Core i7-13700E 16C (8P+8E)/24T, 1.9 (5.1) GHz, 30 MB cache; Core i7-13700TE 16C (8P+8E)/24T, 1.1 (4.8) GHz, 30 MB cache; Core i5-13500E 14C (6P+8E)/20T, 2.4 (4.6) GHz, 24 MB cache
Chipset	Intel R680E
Graphic	
Graphics controller	Intel UHD Graphics 770 (Core i5, Core i7, Core i9)
Drives	
SSD	Yes; base module: 480 GB 2.5" SATA SSD (PLP); 960 GB 2.5" SATA SSD (PLP); 512 GB 2.5" SATA SSD; 1 TB 2.5" SATA SSD; 512 GB M.2 NVME onboard SSD; 1 TB M.2 NVME onboard SSD; 512 GB M.2 NVME onboard SSD with 1* 512 GB M.2 NVME on 1 exchangeable SSD slider; 512 GB M.2 NVME onboard SSD with 1* 1 TB M.2 NVME on 1 exchangeable SSD slider; RAID1 2* 512 GB M.2 NVME on 2 exchangeable SSD slider; RAID1 2* 1 TB M.2 NVME on 2 exchangeable SSD slider; 512 GB M.2 NVME onboard SSD with RAID1 2* 512 GB M.2 NVME on 2 exchangeable SSD slider
Memory	
Type of memory	DDR5-4800 SO-DIMM
Main memory	8 / 16 / 32 / 64 GB; ECC optional
Capacity of main memory, max.	64 Gbyte
Data areas and their retentivity	
Retentive data area (incl. timers, counters, flags), max.	512 kbyte; 128 KB can be stored in the buffer time
Interfaces	
Number of industrial Ethernet interfaces	4; 4x Gigabit Ethernet (RJ45)
USB port	1x USB 3.2 Gen2 10G Type C, 6x USB 3.2 Gen 2 10G Type A
Connection for keyboard/mouse	USB / USB
Multimedia	
• Audio In/Out	Yes
Video interfaces	
• Graphics interface	2x DisplayPort
Industrial Ethernet	
• Industrial Ethernet interface	4x Gigabit Ethernet (RJ45)
— 100 Mbps	Yes
— 1000 Mbps	Yes
Integrated Functions	
Monitoring functions	
• Temperature monitoring	Yes
• Watchdog	Yes

• Fan	Yes
• Monitoring function via network	Optional
EMC	
Interference immunity against discharge of static electricity	
• Interference immunity against discharge of static electricity	±6 kV contact; ±8 kV air (to IEC 1000-4-2; ESD)
Interference immunity against high-frequency electromagnetic fields	
• Interference immunity against high frequency radiation	10 V/m, 80 MHz to 2 700 MHz, 80 % AM acc. to IEC 61000-4-3; 3 V/m, 2.7 GHz to 6 GHz, 80 % AM acc. to IEC 61000-4-3; 10 V, 10 kHz to 80 MHz, 80 % AM acc. to IEC 61000-4-6
Interference immunity to cable-borne interference	
• Interference immunity on supply cables	±2 kV (according to IEC 61000-4-4, burst); ±1 kV (according to IEC 61000-4-5, surge pulse/line to line); ±2 kV (according to IEC 61000-4-5, surge pulse/line to ground)
• Interference immunity on signal cables >30m	burst: ±2 kV (5 kHz / 100 kHz) in accordance with IEC 61000-4-4; length of signal port extension cable ≥ 30 m; surge: ±2 kV line-to-earth in accordance with IEC 61000-4-5; length of signal port extension cable ≥ 10 m
• Interference immunity on signal cables < 30m	burst: ±1 kV (5 kHz / 100 kHz) in accordance with IEC 61000-4-4; length of signal port extension cable < 30 m; surge: ±2 kV line-to-earth in accordance with IEC 61000-4-5; length of signal port extension cable ≥ 10 m
Interference immunity to magnetic fields	
• Interference immunity to magnetic fields at 50 Hz	100 A/m; to IEC 61000-4-8
Emission of conducted and non-conducted interference	
• Interference emission via line/AC current cables	EN 61000-6-3, EN 61000-6-4, CISPR 22 Class B, FCC Class A
Compliance with line harmonic distortion limits	
• Compliance with line harmonic distortion acc. to IEC 61000-3-2, IEC 61000-3-3	Yes; EN 61000-3-2 Class D; EN 61000-3-3
Degree and class of protection	
IP degree of protection	IP20 with fan, IP40 without fan
Standards, approvals, certificates	
CE mark	Yes; also UKCA
cULus	Yes
RCM (formerly C-TICK)	Yes
FCC	Yes
EMC	EMC EN 61000-6-1, EN IEC 61000-6-1, EN 61000-6-2, EN IEC 61000-6-3, EN IEC 61000-6-4
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	55 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Relative humidity	
• Relative humidity	tested according to IEC 60068-2-78, IEC 60068-2-30: operation: 5 % to 85 % at 30 °C (no condensation) storage: 5 % to 95 % at 25 °C / 55 °C (no condensation)
Vibrations	
• Vibration resistance during operation acc. to IEC 60068-2-6	tested in accordance with IEC 60068-2-6; operation - base module (5 to 8.4 Hz: 3.5 mm; 8.4 to 200 Hz: 9.8 m/s²); extension module w/o storages (10 to 58 Hz: 0.0375 mm; 58 to 200 Hz: 4.9 m/s²); extension module with HDD (10 to 58 Hz: 0.015 mm; 58 to 200 Hz: 1.96 m/s²); extension module with SSD (10 to 58 Hz: 0.0375 mm; 58 to 200 Hz: 4.9 m/s²); storage / transport - 5 to 8.4 Hz: 3.5 mm; 8.4 to 500 Hz: 9.8 m/s²
Shock testing	
• Shock load during operation	tested in accordance with IEC 60068-2-27; operation - base module (150 m/s², 11 ms); extension module w/o HDD (150 m/s², 11 ms); extension module with HDD (10 m/s², 20 ms); storage / transport - 250 m/s², 6 ms
Operating systems	
pre-installed operating system	Windows 10 Enterprise 2021 LTSC 64-bit, MUI
without operating system	Yes; Optional
pre-installed operating system	
• Windows 10 Enterprise	Yes; Windows 10 Enterprise 2021 LTSC 64-bit, MUI
Dimensions	
Width	79 mm
Height	194 mm

Depth	237 mm				
Approvals / Certificates					
General Product Approval				Environment	
 RCM	 EG-Konf.		 UL		

last modified: 1/15/2025 