

SIMATIC IPC PX-32A 19" ST Singletouch 4 x USB 3.2 (back), Ethernet (10/100/1000) Intel Xeon W-11155MLE (1.8/3.1 GHz, 4C/8T); 8 GB; M.2 SSD 256 GB Eco; without 2nd mass storage; Windows 10 IoT Enterprise 2021 LTSC for Celeron processors, W-11155MLE, W-11555MLE; in addition 1 x Com (RS232/485/422) (3 in total) USB restore stick with D&D and software image (if selected) 9-36 V DC industrial power supply (wide range)

Display	
Design of display	19" TFT touch
Screen diagonal	19.1 in
Resolution (pixels)	
• Horizontal image resolution	1 366 pixel
• Vertical image resolution	768 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Input device	
• Mouse, at front	No
Keyboard fonts	
• Function keys	No
• alphanumeric keyboard	No
Touch operation	
• Design as touch screen	Yes
Installation type/mounting	
central design	Yes
distributed design	No
Mounting in portrait format possible	No
Power loss	
In full configuration	83 W
Dimensions	
Width of the housing front	473 mm
Height of housing front	297 mm
Mounting cutout, width	455 mm
Mounting cutout, height	279.2 mm
Overall depth	96 mm
Weights	
Weight, approx.	7 kg
Approvals / Certificates	
General Product Approval	



[Miscellaneous](#)



[BIS CRS](#)

General Product Approval

Dangerous goods

[KC](#)

[Dangerous goods information](#)

