

Article No. : 6SL3111-4VE21-6FA1



Figure similar

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Rated data				
Output	Spindle	Feedrate 1	Feedrate 2	Feedrate 3
Rated output current AC I _N	18.0 A	9.0 A	5.0 A	5.0 A
AC base load current I _H	15.3 A	7.7 A	4.3 A	4.3 A
Intermittent operating current AC I _{S6} (40%)	24.0 A	12.0 A	6.5 A	6.5 A
Peak current AC I _{max}	36.0 A	18.0 A	10.0 A	10.0 A
Rated power: at 540 V DC link voltage	8.7 kW	4.3 kW	2.4 kW	2.4 kW
Rated power: at 600 V DC link voltage	9.7 kW	4.8 kW	2.7 kW	2.7 kW

Input	
Number of phases	3 AC
Line voltage	380 ... 460 V ±10 %
Line frequency	45 ... 66 Hz
DC electronic power supply	24 V (20.4 ... 28.8 V)
Electronics current consumption at DC 24 V	
without external fan assembly	1.6 A
with external fan assembly	2.4 A
Rated current	
at 3AC 400 V	28.0 A
at 3AC 380 V / 480 V	29.0 A / 25.0 A
at 3AC 400 V I _{S6} (40%)	35.5 A
at 3AC 400 V peak current	56.0 A

Infeed	
Rated power P _N (S1)	16.0 kW
Feed-in power P _{S6} (40%)	21.0 kW
Feed-in peak power P _{max}	35.0 kW

Output	
Number of phases	3 AC
Rated voltage	0 ... 0.7 x DC link voltage
Pulse frequency	4 kHz
Electronic output current for extension axis DC 24	20.0 A

Output for extension axis	
DC link output current DC I _N	40.0 A
DC link voltage	510 ... 720 V

Energy recovery	
Rated power P _N (S1)	16.0 kW
Feed-in peak power P _{max}	35.0 kW
DC link capacitance	1,645 µF
DC link voltage	460 ... 720 V
DC overvoltage cut-off	820 V ±2 %
DC undervoltage cut-off	380 V ±2 %
Mains fuse	AJT35
I _n fuse	35.0 A
Circuit breaker rated current	50.0 A
Resulting rated short-circuit current SCCR at 480 V AC	65 kA
Resulting rated short-circuit current SCCR at 600 V AC	200 kA

General tech. specifications	
Power factor	0.65 ... 0.90
Displacement angle cos φ	0.96
Power loss	
Total	492 W
Internal	87 W
External	405 W

Ambient conditions	
Cooling	External air cooling
Cooling air requirement	160 m³/h (5,650.35 ft³/h)
Installation altitude (without derating)	1,000 m (3,280.84 ft)
Ambient temperature	
during operation, max.	45 °C (113 °F)
The specified values refer to operation without derating	



Data sheet for SINAMICS S120 Combi

Article No. : 6SL3111-4VE21-6FA1

Mechanical data	
Degree of protection	IP20 / UL open type
Net weight	18.9 kg (41.58 lb)
Dimensions	
Width	305 mm (12.01 in)
Height	410 mm (16.14 in)
Depth	260 mm (10.24 in)
Standards	
Compliance with standards	CE, cURus
Safety Integrated	SIL 2 acc. to IEC 61508, PL d acc. to EN ISO 13849-1, Category 3 acc. to EN ISO 13849-1