



busbar system busbar center-to-center spacing 60 mm device adapter, width: 45 mm busbar thickness: 5.10 mm+TT profile with 1 mounting rail 35 mm, for 3RA6 compact starter, length 200 mm Ue 690 V, Ie up to 32 A, notice: if rated current >12 A and short-circuit current > 25 kA max. conductor cross-section 6 mm² and minimum conductor length 2 m must be observed

Model	
product brand name	SENTRON
product designation	Device adapter
design of the product	Accessories
Connections	
type of electrical connection	AWG 10
Mechanical Design	
height	200 mm
width of the adapter	108 mm
depth	63 mm
thickness of the busbar	
• minimum	5 mm
busbar center-to-center spacing	60 mm
Net Weight	310 g

Approvals Certificates		
General Product Approval	Test Certificates	Maritime application



[Miscellaneous](#)



other	Environment
-------	-------------



[Confirmation](#)

[Miscellaneous](#)

[Environmental Con-
firmations](#)

[Environmental Con-
firmations](#)

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1211-1NS10>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/8US1211-1NS10>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1211-1NS10
- CAX-Online-Generator
<http://www.siemens.com/cax>
- Tender specifications

last modified:

4/8/2025 

