

busbar system, accessory busbar center-to-center spacing 40 mm busbar support 3-pole 12x 5, 2x12x 5.15x 5, 2x15x 5 as end and intermediate holder incl. inlay components for busbar thickness 5 mm and incl. end covers



Figure similar

Model		
product brand name	SENTRON	
product designation	busbar support	
operating voltage at AC rated value	690 V	
type of connectable conductor cross-sections for copper conductor stranded	12 mm x 5 mm - 15 mm x 10 mm	
Mechanical Design		
busbar center-to-center spacing	40 mm	
Net Weight	177 g	
Approvals Certificates		
General Product Approval	Test Certificates	other



[Miscellaneous](#)



[Miscellaneous](#)

other	Environment
Confirmation	Environmental Confirmations
	Environmental Confirmations

Further information

- Information on the packaging
<https://support.industry.siemens.com/cs/ww/en/view/109813875>
- Information- and Downloadcenter (Catalogs, Brochures,...)
<http://www.siemens.com/lowvoltage/catalogs>
- Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8US1903-3AB00>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/8US1903-3AB00>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8US1903-3AB00
- CAX-Online-Generator
<http://www.siemens.com/cax>
- Tender specifications
<http://www.siemens.com/specifications>

