



plug-in relay complete unit, 1 changeover contact, 24 V DC, LED module red, standard plug-in socket screw terminal, 3.5 mm pinning

product brand name	SIRIUS
product designation	Coupling relay with plug-in relay
product type designation	LZS
General technical data	
display version LED	Yes
consumed active power	0.4 W
percental drop-out voltage related to the input voltage	10 %
operating frequency without load	36 000 1/h
operating frequency with load	360 1/h
switching behavior	monostable
mechanical service life (operating cycles) typical	30 000 000
electrical endurance (operating cycles) at AC-15 at 230 V typical	100 000
thermal current	16 A
reference code according to IEC 81346-2	K
Substance Prohibitance (Date)	05/01/2012
Weight	0.058 kg
Control circuit/ Control	
control supply voltage at DC rated value	24 V
closing delay	
• at DC maximum	8 ms
opening delay	
• at DC maximum	6 ms
Switching Function	
design of the switching function	changeover switch
Mechanical data	
product component plug-in socket	Yes
design of the snap-on socket base	Standard socket
design of the relay operating mechanism	poled
Short-circuit protection	
design of the fuse link for short-circuit protection of the auxiliary switch required	fuse gG: 10 A
Auxiliary circuit	
type of switching contact	Changeover contact
material of switching contacts	AgNi 90/10
number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	0
number of CO contacts for auxiliary contacts	1
Main circuit	
type of voltage	DC

Display		
display version as status display by LED	LED red	
Connections/ Terminals		
product function removable terminal	No	
type of electrical connection	screw terminal	
type of connectable conductor cross-sections	<ul style="list-style-type: none"> • solid 1x (1,0 ... 2,5), 2x 1,0, 2x 1,5, 2x 2,5 • finely stranded with core end processing 1x (1.0 ... 1.5), 2x 1.0, 2x 1.5 • for AWG cables solid 1x (18 ... 14), 2x 18, 2x 16, 2x 14 	
connectable conductor cross-section	<ul style="list-style-type: none"> • solid 1 ... 2.5 mm² • finely stranded with core end processing 1 ... 1.5 mm² 	
AWG number as coded connectable conductor cross section	<ul style="list-style-type: none"> • solid 18 ... 14 	
tightening torque with screw-type terminals	0.5 ... 0.7 N·m	
Installation/ mounting/ dimensions		
mounting position	any	
fastening method	snap-on mounting	
height	78 mm	
width	15.5 mm	
depth	71 mm	
Ambient conditions		
ambient temperature	<ul style="list-style-type: none"> • during operation -40 ... +70 °C • during storage -20 ... +70 °C • during transport -20 ... +70 °C 	
Approvals Certificates		
General Product Approval	Test Certificates	other
    Type Test Certificates/Test Report 		
other	Environment	
Confirmation	Environmental Confirmations	
Further information		
<p>Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875</p> <p>Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10</p> <p>Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=LZS:RT3A4L24</p> <p>Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZS:RT3A4L24</p> <p>Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/LZS:RT3A4L24</p> <p>Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZS:RT3A4L24&lang=en</p>		



