

Control Power Transformer, 2000va, PRI 208/230/460v, SEC 115v, Domestic,



Figure similar

|                         |                           |
|-------------------------|---------------------------|
| Product brand name      | Control Power Transformer |
| Design of the product   | Control power voltage     |
| Special product feature | Robust design             |

| General technical data   |                    |
|--|--------------------|
| Weight [lb]  | 38 lb              |
| Height x Width x Depth [in]  | 6.62 × 7 × 7.61 in |
| Ambient temperature [°F]   | -4 ... +104 °F     |
| <ul style="list-style-type: none"> <li>during operation</li> </ul> |                    |
| Ambient temperature  | -20 ... +40 °C     |
| <ul style="list-style-type: none"> <li>during operation</li> </ul> |                    |
| Country of origin  | Mexico             |
| Operating apparent output rated value                              | 2000 V·A           |

| Enclosure             |      |
|-----------------------|------|
| Design of the housing | Open |

| Mounting/wiring   |                  |
|-------------------|------------------|
| Mounting position | Any              |
| Mounting type     | Surface mounting |

|   |                                  |
|---|----------------------------------|
| Type of electrical connection at input for main current circuit | Screw-type terminals (touchsafe) |
|---|----------------------------------|

### Inputs/ Outputs

|  |                         |
|--|-------------------------|
| Input dimensions of primary voltage            | 208/230/460vac          |
| Output dimensions of secondary voltage         | 115vac                  |
| Design of fuse holder of the secondary section | Require touchsafe cover |
| Phase number of the inputs                     | 1                       |
| Electrical input frequency                     | 50 ... 60 Hz            |
| Input voltage _1                               | 208 V                   |
| Input voltage _2                               | 230 V                   |
| Input voltage _3                               | 460 V                   |
| Phase number of the outputs                    | 1                       |
| Electrical output frequency                    | 60 ... 50 Hz            |
| Output voltage _1 rated value                  | 115 V                   |
| Certificate of suitability                     | UL / CSA                |

### Further information

**Industrial Controls - Product Overview (Catalogs, Brochures,...)**

[www.usa.siemens.com/iccatalog](http://www.usa.siemens.com/iccatalog)

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/us/Catalog/product?mfb=US2:MT2000G>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/US/en/ps/US2:MT2000G>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mfb=US2:MT2000G&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=US2:MT2000G&lang=en)

**Certificates/approvals**

<https://support.industry.siemens.com/cs/US/en/ps/US2:MT2000G/certificate>

**last modified:** 11/15/2019