

# Product data sheet

Specifications

SQUARE D



Transformer, drive isolation, dry, 275kVA, 3 phase, 460V delta primary, 460Y/265V secondary, 25D, 150C rise

275T145HDIT

**Product availability:** Non-Stock - Not normally stocked in distribution facility

## Main

Product	Drive Isolation Transformer
Enclosure Code	25D
Enclosure Type	NEMA 2
Insulation Temperature	428 °F (220 °C)
Phase	3 phase
Primary Voltage	460 V delta
Power Rating	275 kVA
Secondary Voltage	460Y/265 V
Full Capacity Taps	2 5 % 1+ 1-
Temperature Rise	150 °C
Winding Material	Aluminium

## Ordering and shipping details

Category	US10PE216266
Discount Schedule	OPE2
GTIN	785901837886
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	49.64 in (126.086 cm)
Package 1 Width	38.07 in (96.698 cm)
Package 1 Length	41.00 in (104.14 cm)
Package weight(Lbs)	1505.267 lb(US) (682.777 kg)

## Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant
REACH Regulation	<a href="#">REACH Declaration</a>
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Use Again

#### Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No