

# Product data sheet

Specifications

SQUARE D



Transformer, dry type, encapsulated, 30kVA, 3 phase, 480V primary, 208Y/120V secondary, 16C, 115C rise [TAA]

30T2F

**Product availability:** Stock - Normally stocked in distribution facility

## Main

Product or Component Type	Dry Sealed Transformer
Primary to Secondary Voltage	480 V delta 208Y/120 V
Full Capacity Taps	2.5 % FCBN

## Complementary

Enclosure Code	16C
Phase	3 phase
Power Rating	30 kVA
Temperature rise	115 °C
Height	22 in (558.8 mm)
Width	25 in (635 mm)
Depth	13.5 in (342.9 mm)
Enclosure mounting	Wall mounted
Enclosure Material	Painted sheet steel

## Environment

Enclosure Type	NEMA 3R
Insulation temperature	356 °F (180 °C)
Product Certifications	cULus CSA UL Listed

## Ordering and shipping details

Category	US10PE216277
Discount Schedule	0PE2
GTIN	785901039402
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Package 1 Height	22.00 in (55.88 cm)
Package 1 Width	25.0 in (63.5 cm)
Package 1 Length	13.50 in (34.29 cm)
Package weight(Lbs)	780.0005 lb(US) (353.802 kg)

---

## Contractual warranty

---

Warranty	18 months
----------	-----------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="#">www.P65Warnings.ca.gov</a>
PVC free	Yes

## Use Again

### Repack and remanufacture

Circularity Profile	No need of specific recycling operations
Take-back	No
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.