

# Product data sheet

Specifications

SQUARE D



Low voltage transformer, non ventilated dry type, 3 phase, 30kVA, 480V primary, 208Y/120V secondary, Type 3R

30T3HNV

Product availability: Non-Stock - Not normally stocked in distribution facility

## Main

Product	Non-Ventilated Transformer
Enclosure Code	19E
Insulation Temperature	428 °F (220 °C)
Phase	3 phase
Primary Voltage	480 V delta
Power Rating	30 kVA
Secondary Voltage	208Y/120 V
Full Capacity Taps	6 2.5 % 2+ 4-
Temperature Rise	150 °C
Winding Material	Aluminium

## Ordering and shipping details

Category	US10PE216273
Discount Schedule	0PE2
GTIN	785901181316
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	42.91 in (109.0 cm)
Package 1 Width	31.42 in (79.8 cm)
Package 1 Length	21.18 in (53.8 cm)
Package weight(Lbs)	396.001 lb(US) (179.623 kg)

## Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.


## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.


[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	No
Packaging without single use plastic	No
<a href="#">EU RoHS Directive</a>	Compliant
REACH Regulation	<a href="#">REACH Declaration</a>
California proposition 65	<b>WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a></b>

### Use Again

 <b>Repack and remanufacture</b>	
Circularity Profile	No need of specific recycling operations
Take-back	No