



Transformer, dry type, encapsulated, 10kVA, 1 phase, 480V primary, 120/240V secondary, 52X, 115C rise [TAA]

4X10S40FSS

Product availability: Non-Stock - Not normally stocked in distribution facility

### Main

| Product or Component Type    | Dry Sealed Transformer |  |
|------------------------------|------------------------|--|
| Primary to Secondary Voltage | 480 V 120/240 V        |  |
| Full Capacity Taps           | 2 5 % FCBN             |  |

## Complementary

| Enclosure Code     | 52X                  |
|--------------------|----------------------|
| Phase              | 1 phase              |
| Power Rating       | 10 kVA               |
| Temperature rise   | 115 °C               |
| Height             | 12 in (304.8 mm)     |
| Width              | 13.75 in (349.25 mm) |
| Depth              | 13.75 in (349.25 mm) |
| Enclosure mounting | Wall mounted         |
| Enclosure Material | Stainless Steel      |

### **Environment**

| Enclosure Type         | NEMA 4X                   |
|------------------------|---------------------------|
| Insulation temperature | 356 °F (180 °C)           |
| Product Certifications | CSA<br>cULus<br>UL Listed |

## Ordering and shipping details

| Category          | US10PE216277  |
|-------------------|---------------|
| Discount Schedule | 0PE2          |
| GTIN              | 3606486438831 |
| Returnability     | No            |
| Country of origin | US            |

## **Packing Units**

| Unit Type of Package 1 | PCE |
|------------------------|-----|
| Nbr. of units in pkg.  | 1   |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| Package 1 Height    | 13.25 in (33.655 cm)        |  |
|---------------------|-----------------------------|--|
| Package 1 Width     | 11.25 in (28.575 cm)        |  |
| Package 1 Length    | 14.25 in (36.195 cm)        |  |
| Package weight(Lbs) | 165.0007 lb(US) (74.843 kg) |  |

# Compliance

Compliance TAA

# **Contractual warranty**

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

## ☑ Environmental footprint

Environmental Disclosure

Product Environmental Profile

### **Use Better**

| Packaging made with recycled cardboard | Yes   |
|--|---|
| Packaging without single use plastic   | No  |
| EU RoHS Directive                      | Compliant   |
| California proposition 65              | WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| PVC free                               | Yes   |

### **Use Again**

| ○ Repack and remanufacture |  |
|----------------------------|--|
| Circularity Profile        | No need of specific recycling operations |
| Take-back                  | No                                       |