



Transformer, dry type, encapsulated, 7.5kVA, 1 phase, 480V primary, 120/240V secondary, 52X, 115C rise [TAA]

4X7S40FSS

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Dry Sealed Transformer	
Primary to Secondary Voltage	480 V 120/240 V	
Full Capacity Taps	2 5 % FCBN	

Complementary

Enclosure Code	52X
Phase	1 phase
Power Rating	7.5 kVA
Temperature rise	115 °C
Height	12 in (304.8 mm)
Width	13.75 in (349.25 mm)
Depth	13.75 in (349.25 mm)
Enclosure mounting	Wall mounted
Enclosure Material	Stainless Steel

Environment

Enclosure Type	NEMA 4X
Insulation temperature	356 °F (180 °C)
Product Certifications	cULus UL Listed CSA

Ordering and shipping details

Category	US10PE216277
Discount Schedule	0PE2
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	13 25 in (33 655 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Width	11.25 in (28.575 cm)	
Package 1 Length	14.25 in (36.195 cm)	
Package weight(Lbs)	135.0002 lb(US) (61.235 kg)	

Compliance

Compliance TAA

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability

0	Environmental footprint	
V	Environmental tootprint	

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACh Regulation	REACh Declaration
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No