

# Product data sheet

## Characteristics

# 8501NR82B

Plug in relay, Type N, relay socket, 11 blade, double tier, for 8510KU relays, bulk packaged



### Main

[In] rated current 15 A 300 V AC

## Complementary

Mounting type	Panel DIN rail
Electrical connection	Double tiered screw clamp terminals
Package quantity	Set of 10
Width	1.7 in (43 mm)
Height	3.1 in (80 mm)
Depth	1.02 in (26 mm)

## Ordering and shipping details

Category	US10CP221142
Discount Schedule	0CP2
GTIN	785901006091
Returnability	Yes
Country of origin	CN

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.0000000000 in (2.54 cm)
Package 1 Width	1.700 in (4.318 cm)
Package 1 Length	3.100 in (7.874 cm)
Package 1 Weight	2.080 oz (58.967 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	2.100 in (5.334 cm)
Package 2 Width	3.200 in (8.128 cm)
Package 2 Length	8.50 in (21.59 cm)
Package 2 Weight	21.120 oz (598.741 g)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)  <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

## Contractual warranty

Warranty	18 months
----------	-----------