

Product data sheet

Characteristics

8501XMO60V02

NEMA Control Relay, Type X, master, 10A resistive at 600VAC, 6 normally open contacts, 110/120VAC 50/60Hz coil



Main

Range	8501X
Relay Type	Master
Product	Relay
Current Rating	20 A AC
Contact Configuration	6 NO 6 master contact cartridges
Number of Poles	6P
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz
Voltage Rating	600 V AC
Mounting Type	Panel
Operating Temperature	-40.000000...71.1 °C (-40...160 °F)
Electrical Connection	Screw clamp terminals
Certifications	CSA[RETURN]UL Listed[RETURN]CE
Operating Time	15 ms - pick-up 16 ms - drop-out
Height	3.5 in (88.9 mm)
Width	2.23 in (56.64 mm)
Depth	5.16 in (131.06 mm)

Ordering and shipping details

Category	US10CP221158
Discount Schedule	0CP2
GTIN	785901018247
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.540 in (6.452 cm)
Package 1 Width	1.0000000000 in (2.54 cm)
Package 1 Length	6.452 in (16.387 cm)
Package 1 Weight	2.390 lb(US) (1.084 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration

RoHS exemption information	<input checked="" type="checkbox"/> Yes
Environmental Disclosure	<input checked="" type="checkbox"/> Product Environmental Profile
Circularity Profile	<input checked="" type="checkbox"/> End Of Life Information

Contractual warranty

Warranty	18 months
----------	-----------
