

Product data sheet

Specifications

SQUARE D



NEMA Contactor, Type S, nonreversing, Size 5, 270A, 200HP at 575VAC, 3 phase, up to 100kA, 3 pole, 480VAC coil, open [TAA]

8502SGO2V06

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product Type	Contactor
Product Range	8502S
Contactor Type	Non-reversing

Complementary

NEMA Size	5
Rated Current	270 A
Number of Poles	3P
Maximum Voltage Rating	600 V AC
Phase	3 phase
Horsepower Rating	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC

SCCR	Circuit-breaker 400 A maximum, SCCR: 100 kA at 480 V AC Fuse J 400 A maximum, SCCR: 100 kA at 600 V AC Fuse T 400 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 400 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 400 A maximum, SCCR: 100 kA at 600 V AC
------	---

Coil Voltage	480 V AC 60 Hz 440 V AC 50 Hz
--------------	----------------------------------

Control Circuit Type	Common control circuit
----------------------	------------------------

Control Units	No control units
---------------	------------------

Pilot Light	No indicator
-------------	--------------

Auxiliary Contacts	Uden
--------------------	------

Other Equipment	Fuse not supplied
-----------------	-------------------

Terminal Type	Screw clamp terminals
---------------	-----------------------

Height	12.31 in (312.67 mm)
--------	----------------------

Width	8.67 in (220.22 mm)
-------	---------------------

Depth	8.75 in (222.25 mm)
-------	---------------------

Environmental

Enclosure Type	Not rated (open device)
----------------	-------------------------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Certifications	UL listed file E78351 CCN NLDX CSA
-----------------------	---------------------------------------

Ordering and shipping details

Category	US10CP121194
-----------------	--------------

Discount Schedule	0CP1
--------------------------	------

GTIN	785901851110
-------------	--------------

Returnability	No
----------------------	----

Country of origin	MX
--------------------------	----

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Nbr. of units in pkg.	1
------------------------------	---

Package 1 Height	10.00 in (25.400 cm)
-------------------------	----------------------

Package 1 Width	11.00 in (27.940 cm)
------------------------	----------------------

Package 1 Length	13.70 in (34.798 cm)
-------------------------	----------------------

Package weight(Lbs)	46.310 lb(US) (21.006 kg)
----------------------------	---------------------------

Compliance

Compliance	TAA
-------------------	-----

Contractual warranty

Warranty	18 months
-----------------	-----------

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

 Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Again

 Repack and remanufacture	
Take-back	No