8538SCA24V81FF4T

NEMA Combination Starter, Type S, 30A fusible disconnect, Size 1, 27A, 10HP at 600VAC polyphase, 120VAC coil, NEMA 12



Main

Product	Combination Starter
Туре	S
Control Circuit Type	Control circuit transformer

Complementary

Control Circuit Voltage	120 V AC 60 Hz secondary circuit	
John S. G. Gait Tolkago	480 V AC 60 Hz primary circuit	
Starter Type	Non reversing	
Number of Poles	3P	
Horsepower Rating	10 Hp 460 V AC, 3 phase 10 hp 575 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	Without	
Control Circuit Fusing	2 fuses primary circuit 1 fuse secondary circuit	
Thermal overload type	Melting alloy 3	
Disconnect Type	Fusible disconnect switch H, 30 A	
NEMA size	1	

Environment

Enclosure Type	NEMA 12 painted sheet steel with external reset

Ordering and shipping details

Category	US10CP121213	
Discount Schedule	0CP1	
GTIN	785901021032	
Returnability	Yes	

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	35.59 lb(US) (16.143 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☐ China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------