

Product data sheet

Specifications

SQUARE D



NEMA combination starter, Type S, 30A fusible disconnect, Size 2, 45A, 15HP at 600VAC, 3 phase, 3 pole, Motor Logic SSOLR, 120VAC coil, NEMA 12 [TAA]

8538SDASP5

Product availability: Stock - Normally stocked in distribution facility

Main

| | |
|----------------------|--------------------------|
| Product | Combination Starter |
| Type | S |
| Control Circuit Type | Separate control circuit |

Complementary

| | |
|-------------------------|--|
| Control Circuit Voltage | 110 V AC 50 Hz 120 V AC 60 Hz |
| Starter Type | Non reversing |
| Line Rated Current | 45 A |
| Number of Poles | 3P |
| Horsepower Rating | 15 hp 460 V AC, 3 phase 15 hp 575 V AC, 3 phase |
| Maximum Voltage Rating | 600 V AC |
| Control Units | Selector switch HAND-OFF-AUTO) |
| Pilot Light | Red indicator on LED Green indicator off LED |
| Auxiliary Contacts | 2 NO + 2 NC |
| Thermal overload type | Solid state Motor Logic class 10/20 15...45 A |
| Disconnect Type | Fusible disconnect switch H and K, 30 A, electrical SPDT |
| NEMA size | 2 |
| Height | 27.75 in (704.85 mm) |
| Depth | 9.59 in (243.59 mm) |
| Width | 10.5 in (266.7 mm) |

Environment

| | |
|------------------------|---|
| Enclosure Type | NEMA 12 painted sheet steel with external reset |
| Product Certifications | UL Listed CSA |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10CP121213 |
| Discount Schedule | 0CP1 |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|--------------------------|--------------|
| GTIN | 785901908258 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|-------------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 12.30 in (31.242 cm) |
| Package 1 Width | 14.00 in (35.560 cm) |
| Package 1 Length | 32.50 in (82.550 cm) |
| Package weight(Lbs) | 51.000 lb(US) (23.133 kg) |

Compliance

| | |
|-------------------|-----|
| Compliance | TAA |
|-------------------|-----|

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

|  Materials and Substances | |
|---|---------------------|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | Yes |
| EU RoHS Directive | Under investigation |

Use Again

|  Repack and remanufacture | |
|---|----|
| Take-back | No |