



Contactor, Type LX multipole lightling, mechanically held, 30A, 8 pole, 600V, 110/120VAC 50/60Hz coil, NEMA 1 [TAA]

8903LXG80V02CR6

Product availability: Non-Stock - Not normally stocked in distribution facility

Main

Product or Component Type	Mechanically Held Lighting Contactor	
Range of Product	8903LX	
Control Circuit	Separate control circuit	

Complementary

oompromontar j	omprementary		
Control Voltage	110 V AC 50 Hz 120 V AC 60 Hz		
Inrush power in VA	140 VA 60 Hz 150 VA 50 Hz 180 VA 50/60 Hz		
Current Rating	20 A tungsten 30 A fluorescent		
Number of Poles	8P 8 NO		
Control Unit	Selector switch HAND-OFF-AUTO)		
Pilot Light	No indicator		
Other Options	2P relay (1 NO + 1 NC)		
Electrical Connection	Screw-clamp terminals		
Height	12.7 in (322 mm)		
Depth	6.02 in (153 mm)		
Width	7.8 in (198 mm)		

Environment

Enclosure Type	NEMA 1 painted sheet steel surface	
Product Certifications	UL Listed	

Ordering and shipping details

Category	US10CP121322
Discount Schedule	0CP1
GTIN	785901023364
Returnability	No
Country of origin	MX

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	7.50 in (19.05 cm)	
Package 1 Width	8.40 in (21.336 cm)	
Package 1 Length	13.00 in (33.02 cm)	
Package weight(Lbs)	12.200 lb(US) (5.534 kg)	

Compliance

Compliance TAA

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

☑ Environmental footprint

Environmental Disclosure

Product Environmental Profile

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
Halogen content performance	Halogen free plastic parts product
PVC free	Yes

Use Again

○ Repack and remanufacture	
Circularity Profile	No need of specific recycling operations
Take-back	No