

# Product data sheet

Specifications

SQUARE D



Contactor, Type L, multipole lighting, mechanically held, 30A, 8 pole, 600V, 110/120VAC 50/60Hz coil, open style [TAA]

8903LXO80V02

**Product availability:** Stock - Normally stocked in distribution facility

## Main

|                           |                                      |
|---------------------------|--------------------------------------|
| Product or Component Type | Mechanically Held Lighting Contactor |
| Range of Product          | 8903LX                               |
| Control Circuit           | Separate control circuit             |

## Complementary

|                       |   |
|-----------------------|---|
| Control Voltage       | 110 V AC 50 Hz<br>120 V AC 60 Hz                |
| Inrush power in VA    | 140 VA 60 Hz<br>150 VA 50 Hz<br>180 VA 50/60 Hz |
| Current Rating        | 20 A tungsten<br>30 A fluorescent               |
| Number of Poles       | 8P 8 NO   |
| Control Unit          | No control units                                |
| Pilot Light           | No indicator                                    |
| Other Options         | None  |
| Electrical Connection | Screw-clamp terminals                           |
| Height                | 8.8 in (224 mm)                                 |
| Depth                 | 3.3 in (83 mm)                                  |
| Width                 | 5.6 in (143 mm)                                 |

## Environment

|                        |                         |
|------------------------|-------------------------|
| Enclosure Type         | Not rated (open device) |
| Product Certifications | UL Listed<br>CSA        |

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US10CP121322 |
| Discount Schedule | OCP1         |
| GTIN              | 785901057406 |
| Returnability     | Yes          |
| Country of origin | MX           |

## Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                                     |                              |
|-------------------------------------|------------------------------|
| <b>Unit Type of Package 1</b>       | PCE                          |
| <b>Nbr. of units in pkg.</b>        | 1                            |
| <b>Package 1 Height</b>             | 4.50 in (11.430 cm)          |
| <b>Package 1 Width</b>              | 7.40 in (18.796 cm)          |
| <b>Package 1 Length</b>             | 10.50 in (26.670 cm)         |
| <b>Package weight(Lbs)</b>          | 5.300 lb(US) (2.404 kg)      |
| <b>Unit Type of Package 2</b>       | PAL                          |
| <b>Number of Units in Package 2</b> | 90                           |
| <b>Package 2 Height</b>             | 40.00 in (101.600 cm)        |
| <b>Package 2 Width</b>              | 40.00 in (101.600 cm)        |
| <b>Package 2 Length</b>             | 48.00 in (121.920 cm)        |
| <b>Package 2 Weight</b>             | 486.0006 lb(US) (220.446 kg) |

## Compliance

|            |     |
|------------|-----|
| Compliance | TAA |
|------------|-----|

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Environmental Disclosure

[Product Environmental Profile](#)

## Use Better

### Materials and Substances

|  |  |
|--|--|
| Packaging made with recycled cardboard | Yes  |
| Packaging without single use plastic   | No   |
| <a href="#">EU RoHS Directive</a>      | Compliant  |
| California proposition 65              | WARNING: Cancer and Reproductive Harm - <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| Halogen content performance            | Halogen free plastic parts product   |
| PVC free                               | Yes  |

## Use Again

### Repack and remanufacture

|                     |  |
|---------------------|--|
| Circularity Profile | No need of specific recycling operations |
| Take-back           | No                                       |