

Product data sheet

Specifications

SQUARE D



Contactor, Type S, multipole lighting, electrically held, 30A, 3 pole, 110/120VAC 50/60Hz coil, open style [TAA]

8903SM02V02

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Electrically Held Lighting Contactor
Type	S

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Current Rating	30 A
Number of Poles	3P
Control Units	No control units
Pilot Light	Without pilot light
Auxiliary Contacts	Uden
Other Options	None
Electrical Connection	Lugs
Height	3.5 in (89 mm)
Depth	4.2 in (107 mm)
Width	3.2 in (82 mm)

Environment

Enclosure Type	Not rated (open device) surface none
Product Certifications	UL Listed CSA

Ordering and shipping details

Category	US10CP121325
Discount Schedule	0CP1
GTIN	785901619529
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	4.50 in (11.430 cm)
Package 1 Width	5.90 in (14.986 cm)
Package 1 Length	8.00 in (20.320 cm)
Package weight(Lbs)	3.150 lb(US) (1.429 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	175
Package 2 Height	40.00 in (101.600 cm)
Package 2 Width	40.00 in (101.600 cm)
Package 2 Length	48.00 in (121.920 cm)
Package 2 Weight	557.0006 lb(US) (252.651 kg)

Compliance

Compliance	TAA
------------	-----

Contractual warranty

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Not compliant

Use Again

Repack and remanufacture

Take-back	No
-----------	----