



Contactor, Type S, multipole lighting, electrically held, 200A, 3 pole, 110/120VAC 50/60Hz coil, open style [TAA]

8903SVO2V02

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Electrically Held Lighting Contactor	
Туре	S	

Complementary

Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz	
Current Rating	200 A	
Number of Poles	3P	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Uden	
Other Options	None	
Electrical Connection	Lugs	
Height	9.1 in (232 mm)	
Depth	6.5 in (165 mm)	
Width	6.0 in (152 mm)	

Environment

Enclosure Type	Not rated (open device) surface none	
Product Certifications	UL Listed CSA	

Ordering and shipping details

Category	US10CP121325
Discount Schedule	0CP1
GTIN	785901626022
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Height	10.70 in (27.178 cm)	
Package 1 Width	10.90 in (27.686 cm)	
Package 1 Length	14.50 in (36.830 cm)	
Package weight(Lbs)	17.480 lb(US) (7.929 kg)	

Compliance

Compliance TAA

Contractual warranty

Warranty 18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Not compliant
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

Use Again

○ Repack and remanufacture		
Take-back	No	