

Product data sheet

Characteristics

8910DPA52V02

Contactor, Definite Purpose, 50A, 2 pole, 10HP at 230VAC, 1 phase, 110/120VAC 50/60Hz coil, open



Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	50 A
Number of Poles	2P
Pole contact composition	2 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	3 Hp 115 V AC, 1 phase 10 hp 230 V AC, 1 phase
Locked rotor rated current	300 A 277 V AC 250 A 460 V AC 200 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	120 V AC 60 Hz 110 V AC 50 Hz
Phase	1 phase
Electrical Connection	Quick connect terminals Box lugs

Environment

Product Certifications	UL Recognized[RETURN]CSA
------------------------	--------------------------

Ordering and shipping details




Category	US1CP1B21345
Discount Schedule	CP1B
GTIN	785901080763
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.800 in (9.652 cm)
Package 1 Width	4.300 in (10.922 cm)
Package 1 Length	2.700 in (6.858 cm)
Package 1 Weight	23.040 oz (653.173 g)
Unit Type of Package 2	CAR
Number of Units in Package 2	8
Package 2 Height	8.200 in (20.828 cm)
Package 2 Width	5.50 in (13.97 cm)

Package 2 Length	8.900 in (22.606 cm)
Package 2 Weight	11.830 lb(US) (5.366 kg)

Offer Sustainability

REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes

Contractual warranty

Warranty	18 months
----------	-----------

Approximate Dimensions

