Product data sheet

Specifications

SQUARE D

Contactor, Definite Purpose, 60A, 3 pole, 30HP at 575VAC, 3 phase, 277VAC 60Hz coil, open

8910DPA63V04

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Definite Purpose Contactor
Line Rated Current	60 A
Number of Poles	3P
Pole contact composition	3 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	5 hp 115 V AC, 1 phase 10 hp 230 V AC, 1 phase 30 hp 460 V AC, 3 phase 30 hp 575 V AC, 3 phase 25 hp 230 V AC, 3 phase
Locked rotor rated current	360 A 277 V AC 300 A 460 V AC 240 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	277 V AC 60 Hz
Phase	3 phase
Electrical Connection	Box lugs Quick connect terminals
Height	4.1 in (105 mm)
Width	2.6 in (65 mm)
Depth	3.7 in (93 mm)

Environment

Product Certifications	UL Recognized CSA

Ordering and shipping details

Category	US1CP1B21346
Discount Schedule	CP1B
GTIN	785901024521
Returnability	Yes
Country of origin	MX

Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.00 in (10.16 cm)
Package 1 Width	4.50 in (11.43 cm)
Package 1 Length	2.80 in (7.112 cm)
Package weight(Lbs)	31.999 oz (907.185 g)

Contractual warranty

Warranty	18 months

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained ⟩

How we assess product sustainability ⟩

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Compliant with Exemptions**

Use Again

Repack and remanufacture

Take-back	**No**

Dimensions Drawings

Approximate Dimensions

Electrical Clearance/Wire Bending Space
Minimum to wall or barrier to ensure adequate wire bending space to lug surface when the maximum wire size is used. Ref. NEC 430-10

2.50 [64]

2.11 [54]

.23 [6]

1.54 [39]

.07 [2]

in. [mm]

.09 [2]

.23 [6]

3.25 [83]

4.06 [103]

3.72 [95]

.51 [13]

2.58 [65]

.24 [8]

3.67 [93]

Life Is On | Schneider Electric

Technical Illustration

Wiring diagram

COIL

L1   L2   L3

T1   T2   T3