



Starter, Definite Purpose, nonreversing, 40A, 2 pole, 1 phase, 208V to 240V AC coil, melting alloy overload, NEMA 1

8911DPSG42V09

Product availability: Stock - Normally stocked in distribution facility

Main

Product	Definite Purpose Starter	
Ampere Rating	40 A	
Horsepower Rating	3 hp 115 V AC, 1 phase 7.5 hp 230 V AC, 1 phase	
Maximum Voltage Rating	600 V AC	
Control Circuit Voltage	220 V AC 50 Hz 208240 V AC 60 Hz	
Phase	1 phase	

Complementary

Enclosure Material	Painted sheet steel	
Enclosure Rating	NEMA 1	
Locked Rotor Amperes	240 A 230 V AC 200 A 460 V AC	
Number of Poles	160 A 575 V AC 2P	
Range	DPS	
Overload Type	Melting alloy	
Number of Thermal Units	1	

Ordering and shipping details

Category	US10CP121381
Discount Schedule	0CP1
GTIN	785901724766
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Nbr. of units in pkg.	1	
Package 1 Height	6.500 in (16.510 cm)	
Package 1 Width	7.000 in (17.780 cm)	
Package 1 Length	11.300 in (28.702 cm)	

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package weight(Lbs)

5.829 lb(US) (2.644 kg)

Contractual warranty

Warranty

18 months



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

Materials and Substances	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions

Use Again

○ Repack and remanufacture		
Take-back	No	