

# Product data sheet

Specifications

SQUARE D



NEMA starter, Definite Purpose, 25A, 20HP at 600VAC, 3 phase, 3 pole, melting alloy, 208V to 240VAC coil, open

8911DPSO23V09

**Product availability:** Stock - Normally stocked in distribution facility

## Main

Product	Definite Purpose Starter
Ampere Rating	25 A
Horsepower Rating	2 hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase 10 hp 230 V AC, 3 phase 15 hp 460 V AC, 3 phase 20 hp 575 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Circuit Voltage	220 V AC 50 Hz 208...240 V AC 60 Hz
Phase	3 phase

## Complementary

Enclosure Rating	Not rated (open device)
Locked Rotor Amperes	150 A 230 V AC 125 A 460 V AC 100 A 575 V AC
Number of Poles	3P
Range	DPS
Overload Type	Melting alloy
Number of Thermal Units	3

## Ordering and shipping details

Category	US10CP121381
Discount Schedule	OCP1
GTIN	785901342793
Returnability	Yes
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	4.80 in (12.192 cm)
Package 1 Width	4.80 in (12.192 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Package 1 Length	8.00 in (20.320 cm)
Package weight(Lbs)	2.291 lb(US) (1.039 kg)

---

## Contractual warranty

---

Warranty	18 months
----------	-----------



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

## Use Better

### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions

## Use Again

### Repack and remanufacture

Take-back	No
-----------	----