

Product data sheet

Specifications

SQUARE D



Reversing Hoist Contactor, 30A, 3 pole, 110/120VAC 50/60Hz coil, open style

8965DPR33V02

Product availability: Stock - Normally stocked in distribution facility

Main

Product or Component Type	Reversing Hoist Contactor
Line Rated Current	30 A
Maximum Horse Power Rating	2 hp 115 V AC, 1 phase 5 hp 230 V AC, 1 phase 10 hp 230 V AC, 3 phase 15 hp 460 V AC, 3 phase 15 hp 575 V AC, 3 phase

Complementary

Product Certifications	UL Listed CSA
[Ue] rated operational voltage	600 V AC
Poles description	3P
[Uc] control circuit voltage	110 V AC 50 Hz 120 V AC 60 Hz
Phase	3 phase
Range of Product	DPR

Ordering and shipping details

Category	US10CP121403
Discount Schedule	0CP1
GTIN	785901081364
Returnability	Yes
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.0 in (12.7 cm)
Package 1 Width	5.0 in (12.7 cm)
Package 1 Length	6.50 in (16.51 cm)
Package weight(Lbs)	2.401 lb(US) (1.089 kg)

Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.



Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
EU RoHS Directive	Compliant with Exemptions

Use Again

Repack and remanufacture

Take-back	No
-----------	----