

# Product data sheet

Specifications

**SQUARE D**



## Reversing hoist contactor, 40A, 3 pole, 24VAC 50/60 Hz coil, open style

8965DPR43V14

**Product availability: Stock - Normally stocked in distribution facility**

### Main

Product or Component Type	Reversing Hoist Contactor
Line Rated Current	40 A
Maximum Horse Power Rating	3 hp 115 V AC, 1 phase 7.5 hp 230 V AC, 1 phase 15 hp 230 V AC, 3 phase 20 hp 460 V AC, 3 phase 20 hp 575 V AC, 3 phase

### Complementary

Product Certifications	UL Listed CSA
[Ue] rated operational voltage	600 V AC
Poles description	3P
[Uc] control circuit voltage	24 V AC 50/60 Hz
Phase	3 phase
Range of Product	DPR

### Ordering and shipping details

Category	US10CP121403
Discount Schedule	0CP1
GTIN	785901571568
Returnability	Yes
Country of origin	CN

### Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.00 in (12.7 cm)
Package 1 Width	5.00 in (12.7 cm)
Package 1 Length	6.00 in (15.24 cm)
Package weight(Lbs)	31.999 oz (907.185 g)

### Contractual warranty

Warranty	18 months
----------	-----------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

 <b>Materials and Substances</b>	
Packaging made with recycled cardboard	Yes
Packaging without single use plastic	Yes
<a href="#">EU RoHS Directive</a>	Compliant with Exemptions

### Use Again

 <b>Repack and remanufacture</b>	
Take-back	No