

## 9001K3L35LGG

Illuminated push-button head, Harmony 9001K, metal, metal guard flush, green, 30mm, spring return, LED green, 24-28V



### Main

|                                 |                                  |
|---------------------------------|----------------------------------|
| Range of Product                | Harmony 9001K                    |
| Product or Component Type       | Head for illuminated push-button |
| Device short name               | 9001K                            |
| Mounting diameter               | 1.2 in (30 mm)                   |
| Operator additional information | Metal guard                      |
| Light source                    | Green LED                        |

### Complementary

|                               |                         |
|-------------------------------|-------------------------|
| Bezel material                | Metal                   |
| Shape of signaling unit head  | Round                   |
| Type of operator              | Spring return           |
| Operator profile              | Green flush, unmarked   |
| Bulb base                     | BA 9s                   |
| Light block supply            | Direct 24...28 V AC/DC  |
| Contacts type and composition | Without contact block   |
| Mechanical durability         | 5000000 cycles          |
| Operating position            | Any position            |
| Net Weight                    | 0.366 lb(US) (0.166 kg) |
| Cap/operator or lens colour   | Green                   |
| [Us] rated supply voltage     | 24...28 V               |
| Light source colour           | Green                   |
| Type of operator              | Spring return           |
| Operator profile              | Flush                   |

### Environment

|                                       |                                                                                                                |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Standards                             | JIS C 852<br>EN/IEC 60947-5-4<br>EN/IEC 60947-5-1<br>UL 508<br>JIS C 4520<br>EN/IEC 60947-1<br>CSA C22.2 No 14 |
| Product Certifications                | NEMA[RETURN]JUL 508                                                                                            |
| Protective treatment                  | TC                                                                                                             |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)                                                                                     |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)                                                                                     |
| Vibration resistance                  | 7 gn 2...500 Hz)IEC 60068-2-6                                                                                  |
| Shock resistance                      | 50 gn IEC 60068-2-27                                                                                           |
| Electrical shock protection class     | Class II IEC 61140                                                                                             |

|                           |                                                                       |
|---------------------------|-----------------------------------------------------------------------|
| IP degree of protection   | IP66 IEC 60529                                                        |
| NEMA degree of protection | NEMA 1<br>NEMA 12<br>NEMA 13<br>NEMA 2<br>NEMA 3<br>NEMA 3R<br>NEMA 4 |

## Ordering and shipping details

|                   |              |
|-------------------|--------------|
| Category          | US10CS121426 |
| Discount Schedule | 0CS1         |
| GTIN              | 785901028574 |
| Returnability     | No           |
| Country of origin | MX           |

## Packing Units

|                              |                           |
|------------------------------|---------------------------|
| Unit Type of Package 1       | PCE                       |
| Number of Units in Package 1 | 1                         |
| Package 1 Height             | 5.080 in (12.903 cm)      |
| Package 1 Width              | 2.0000000000 in (5.08 cm) |
| Package 1 Length             | 12.903 in (32.774 cm)     |
| Package 1 Weight             | 8.000 oz (226.796 g)      |

## Offer Sustainability

|                            |                                                                                                                                                                                                                                                                                             |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>                                                                                                                                                                                                                                                           |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)                                                                                                                                                                                                                                  |
| Mercury free               | Yes                                                                                                                                                                                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>                                                                                                                                                                                                                                                      |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                                                                                                                                                                                         |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.                                                                                                                                                                |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|