Product data sheet

Specifications

30mm Push Button, Types K or SK, plastic legend plate, 60 mm diameter, yellow, black letters, marked EMERGENCY STOP

9001KN9330

Product availability: Stock - Normally stocked in distribution facility

Main

Range of Product	Harmony 9001K Harmony 9001SK
Product or Component Type	Marked legend
Accessory / separate part category	Marking accessory
Accessory / separate part destination	Control and signalling units Ø 30 mm (metal range)
Marking	Black EMERGENCY STOP yellow
Label dimensions	Ø 90 mm
User Language	English

Complementary

Material	Aluminium
Net Weight	0.011 lb(US) (0.005 kg)
Size	30 mm
Colour of marking	Black
Background colour	Yellow
Marking	EMERGENCY STOP

Ordering and shipping details

Category	US10CS121433
Discount Schedule	0CS1
GTIN	785901398387
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	0.10 in (0.254 cm)
Package 1 Width	2.40 in (6.096 cm)
Package 1 Length	2.40 in (6.096 cm)
Package weight(Lbs)	0.160 oz (4.536 g)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Contractual warranty

Warranty   18 months

Life Is On | Schneider Electric

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing "Use Better, Use Longer, Use Again" campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Use Better

⊗ Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**Yes**
EU RoHS Directive	**Pro-active compliance (Product out of EU RoHS legal scope)**
SCIP Number	**Ae0c4eb9-0bfb-40a4-851f-5c619fbe777d**
REACh Regulation	**REACh Declaration**
California proposition 65	**WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

↺ Repack and remanufacture

Take-back	**No**

Offer Marketing Illustration

Product benefits / Features

Offer Marketing Illustration

Product benefits / Features

Technical Benefits
Harmony 9001K

Compliant with IEC, UL, CSA, EN and NOM standards, CE marking

-25°C to +70°C operating temperature range

IP66, NEMA 4 rated (Heavy duty, oil tight, waterproof and dust tight without requiring boots)

Contacts and heads designed against vibration (2 to 500 Hz: 7gn), ensuring secure mounting and wiring

American Bureau of Shipping Approved for Marine Applications & meet all US automotive standards

Class I Div. 1 (gas) and Class II Div. 1 (dust) with reed contact blocks

Image of product in real life situation