



### Main

Range of Product	Harmony 9001K
Product or Component Type	Push-button
Device short name	K
Operator profile	Black flush
Operator additional information	Metal guard

### Complementary

Bezel material	Metal
Mounting diameter	1.2 in (30 mm)
Light source	Without
Light block supply	Without supply
Contacts type and composition	2 C/O
[Ie] rated operational current	10 A, AC-15 10 A, DC-13
Contact operation	Standard
Device presentation	Complete product
Cap/operator or lens colour	Black
Operator profile	Flush
Type of operator	Spring return
Size	30 mm

### Environment

Product Certifications	CE[RETURN]UL listed file E42259 CCN NKCR[RETURN]CSA LR 25490 class 3211 03[RETURN]NEMA
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

### Ordering and shipping details

Category	US10CS121426
Discount Schedule	0CS1
GTIN	785901033301
Returnability	No
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.0000000000 in (5.08 cm)
Package 1 Width	2.0000000000 in (5.08 cm)
Package 1 Length	3.50 in (8.89 cm)
Package 1 Weight	7.344 oz (208.199 g)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------