



### Main

Range of Product	Harmony 9001K
Product or Component Type	Push-to-test pilot light
Device short name	K

### Complementary

Bezel material	Metal
Mounting diameter	1.2 in (30 mm)
Lens type	Fresnel plastic
Cap/operator or lens colour	Green
Bulb base	BA 9s
Light block supply	Full voltage 24 V Full voltage 28 V
Shape of screw head	Round
Light source	Incandescent bulb
Operating Mode	Push-to-test
Lens type	Fresnel
[Us] rated supply voltage	24...28 V
Light block supply	Full voltage
Contacts type and composition	1 C/O
Lens material	Polycarbonate
Size	30 mm

### Environment

Product Certifications	CE[RETURN]UL listed file E42259 CCN NKCR[RETURN]CSA LR25490 class 3211 03
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

### Ordering and shipping details

Category	US10CS121426
Discount Schedule	OCS1
GTIN	785901036081
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.080 in (12.903 cm)
Package 1 Width	2.0000000000 in (5.08 cm)
Package 1 Length	12.903 in (32.774 cm)
Package 1 Weight	6.400 oz (181.437 g)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months
----------	-----------