

Product data sheet

Characteristics

9001SK1L1LGGH13

Illuminated push-button, Harmony 9001SK, plastic, plastic guard flush, green, 30mm, spring return, LED green, 110-120V, 1 C/O



Main

Range of Product	Harmony 9001SK
Product or Component Type	Illuminated push-button
Device short name	9001SK
Operator additional information	Plastic guard

Complementary

Bezel material	Plastic
Mounting diameter	1.2 in (30 mm)
Contacts type and composition	1 C/O
Contact operation	Standard
Mechanical durability	5000000 cycles
Device presentation	Complete product
Cap/operator or lens colour	Green
[Us] rated supply voltage	110...120 V
Light block supply	Via integral transformer
Light source colour	Green
Operator profile	Flush
Type of operator	Spring return
Supply frequency	50...60 Hz
Size	30 mm
Bulb base	BA 9s
Light source	LED

Environment

Standards	EN/IEC 60947-1 UL 508 EN/IEC 60947-5-4 JIS C 852 EN/IEC 60947-5-1 CSA C22.2 No 14 JIS C 4520
IP degree of protection	IP66
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13

Ordering and shipping details

Category	US10CS121429
Discount Schedule	OCS1
GTIN	785901680512
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.4 in (6 cm)
Package 1 Width	2.0 in (5 cm)
Package 1 Length	4.5 in (11.5 cm)
Package 1 Weight	4.4 oz (124 g)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------