9001SK1L35L

Illuminated push-button head, Harmony 9001SK, plastic, plastic guard flush, blue, 30mm, spring return, 24-28V



Main

Range of Product	Harmony 9001SK
Product or Component Type	Head for illuminated push-button
Device short name	9001SK

Complementary

Bezel material	Plastic
Mounting diameter	1.2 in (30 mm)
Shape of signaling unit head	Octagonal
Type of operator	Spring return
Operator profile	Blue flush, unmarked
Operator additional information	Plastic guard
Light source	incandescent
Bulb base	BA 9s
Light block supply	Direct 2428 V AC/DC
Contacts type and composition	Without contact block
Standards	UL 508 JIS C 4520 EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C 852 EN/IEC 60947-5-1 CSA C22.2 No 14
Product Certifications	UL 508[RETURN]NEMA[RETURN]CSA LR25490 class 3211 03[RETURN]UL listed file E78403 CCN NKCR
Protective treatment	TC
Protective treatment Ambient Air Temperature for Storage	
	TC
Ambient Air Temperature for Storage	TC -40158 °F (-4070 °C)
Ambient Air Temperature for Storage Ambient Air Temperature for Operation	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C)
Ambient Air Temperature for Storage Ambient Air Temperature for Operation Vibration resistance	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6
Ambient Air Temperature for Storage Ambient Air Temperature for Operation Vibration resistance Shock resistance	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6 50 gn IEC 60068-2-27
Ambient Air Temperature for Storage Ambient Air Temperature for Operation Vibration resistance Shock resistance Electrical shock protection class	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6 50 gn IEC 60068-2-27 Class II IEC 61140
Ambient Air Temperature for Storage Ambient Air Temperature for Operation Vibration resistance Shock resistance Electrical shock protection class IP degree of protection	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6 50 gn IEC 60068-2-27 Class II IEC 61140 IP66 IEC 60529 NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4
Ambient Air Temperature for Storage Ambient Air Temperature for Operation Vibration resistance Shock resistance Electrical shock protection class IP degree of protection NEMA degree of protection	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6 50 gn IEC 60068-2-27 Class II IEC 61140 IP66 IEC 60529 NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3R NEMA 4 NEMA 4 NEMA 4X
Ambient Air Temperature for Storage Ambient Air Temperature for Operation Vibration resistance Shock resistance Electrical shock protection class IP degree of protection NEMA degree of protection	TC -40158 °F (-4070 °C) -13158 °F (-2570 °C) 7 gn 2500 Hz)IEC 60068-2-6 50 gn IEC 60068-2-27 Class II IEC 61140 IP66 IEC 60529 NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3 NEMA 3 NEMA 3 NEMA 4 NEMA 4X 5000000 cycles

[Let rated supply voltage	2428 V
[Us] rated supply voltage	
Light block supply	Full voltage
Operator profile	Flush
Type of operator	Spring return
Size	30 mm
Light source	Incandescent bulb
Ordering and shipping details	
Category	US10CS121429
Discount Schedule	0CS1
GTIN	785901158639
Returnability	No
Country of origin	MX
Packing Units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.080 in (12.903 cm)
Package 1 Width	2.000000000 in (5.08 cm)
Package 1 Length	12.903 in (32.774 cm)
Package 1 Weight	6.400 oz (181.437 g)
Office Constained III.	
Offer Sustainability California proposition 65	WADNING. This product can average you to chamicals including Load and
Camorna proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₽¥Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Contractual warranty		
Warranty	18 months	