



Main

| | |
|---------------------------|----------------------|
| Range of Product | Harmony 9001SK |
| Product or Component Type | Head for push-button |
| Device short name | 9001SK |

Complementary

| | |
|-------------------------------|----------------------------------|
| Bezel material | Plastic |
| Mounting diameter | 1.2 in (30 mm) |
| CAD overall width | 1.8 in (46 mm) |
| CAD overall height | 1.8 in (45 mm) |
| CAD overall depth | 2.7 in (69 mm) |
| Net Weight | 0.209 lb(US) (0.095 kg) |
| Operating position | Any position |
| Shape of signaling unit head | Round |
| Type of operator | Spring return |
| Operator profile | Black mushroom Ø 30 mm, unmarked |
| Mechanical durability | 5000000 cycles |
| Cap/operator or lens colour | Green |
| Operator profile | Projecting |
| Type of operator | Spring return |
| Contacts type and composition | Without contact block |
| Size | 30 mm |

Environment

| | |
|---------------------------------------|--|
| Protective treatment | TC |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Electrical shock protection class | Class II IEC 61140 |
| IP degree of protection | IP66 IEC 60529 |
| NEMA degree of protection | NEMA 1 NEMA 12 NEMA 13 NEMA 2 NEMA 3 NEMA 3R NEMA 4 NEMA 4X |
| Standards | CSA C22.2 No 14 EN/IEC 60947-5-1 EN/IEC 60947-1 EN/IEC 60947-5-4 JIS C 4520 JIS C 852 UL 508 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

| | |
|------------------------|--|
| Product Certifications | NEMA[RETURN]CSA LR25490 class 3211 03[RETURN]UL listed file E78403 CCN NKCR[RETURN]UL 508 |
| Vibration resistance | 7 gn 2...500 Hz)IEC 60068-2-6 |
| Shock resistance | 50 gn IEC 60068-2-27 |

Ordering and shipping details

| | |
|-------------------|--------------|
| Category | US10CS121429 |
| Discount Schedule | OCS1 |
| GTIN | 785901042709 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.620 in (19.355 cm) |
| Package 1 Width | 3.0000000000 in (7.62 cm) |
| Package 1 Length | 19.355 in (49.161 cm) |
| Package 1 Weight | 8.000 oz (226.796 g) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| WEEE | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|