



**Note:**

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

**9007C54B2M11**



Telemecanique Sensors  
 1875 Founders Drive  
 Dayton, OH 45420-4017  
 Customer Care Center : 1-800-435-2121  
 Web : www.tesensors.com

**Technical Information:**

Terminal Type: Screw Clamp  
 Enclosure Rating: NEMA 1/2/4/6/6P/12/13  
 Approvals: UL# E42259 CCN NKCR - CSA # LR25490 Class 3211-03 - CE Marked  
 Weight: 1.25 lb  
 Conforming to Standards: NEMA and UL type 6P, NOM, ANCE  
 RoHS: No  
 Operating Temperature Range: -20 to 185 °F  
 Shock Resistance: 60 gn (9ms)  
 Vibration Resistance: 25 gn (10-150 Hz, 11 ms)  
 Max. Actuation Speed : 15.2 mpm / 27.4mpm (50 fpm / 90 fpm) + 45 degree cam, levers only  
 Repeat Accuracy: 0.05mm (+/- 0.002 in.)  
 Operating Torque/Force: 4 in-Pounds  
 Cable Length:

**Specification:**

Description: std. rotary spring rtn std pretravel CW+CCW  
 Body Style/Type Description: NEMA Square D 9007 Limit Switches 9007C Heavy Duty SemiModular 39mm Metal Body  
 Head Type: 9007B2 rotary spring return, std. pretravel, CW+CCW  
 Lever Arms: Lever Arm (ordered separately)  
 Body with Contact Type: 1 N.O. / 1 N.C. SPDT Snap Action  
 Conduit Thread: M20-20mm  
 Ampere Rating Continuous: 10A  
 Maximum Voltage Rating: 600V  
 Actuation: CW and CCW  
 Actuator Action: Spring Return - standard Pretravel  
 Lever Arm Length:  
 Roller Dimension:  
 Roller Material:  
 Contact Configuration: 1 N.O./1 N.C.  
 Contact Operation: Snap Action  
 Connection Type: Conduit Entrance (M20-20mm)  
 Head Material: Zinc Alloy  
 Positive Opening: No