


Note:

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

9007C54B



Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Terminal Type: Screw Clamp
 Enclosure Rating: NEMA 1/2/4/6/6P/12/13
 Approvals: UL# E42259 CCN NKCR - CSA # LR25490 Class 3211-03 - CE Marked
 Weight: 1.23 lb
 Conforming to Standards: NEMA and UL type 6P, NOM, ANCE
 RoHS: No
 Operating Temperature Range: -20 to 185 °F
 Shock Resistance: 60 gn (9ms)
 Vibration Resistance: 25 gn (10-150 Hz, 11 ms)
 Max. Actuation Speed : 15.2 mpm / 27.4mpm (50 fpm / 90 fpm) + 45 degree cam, levers only
 Repeat Accuracy: 0.05mm (+/- 0.002 in.)
 Operating Torque/Force: 4 in-Pounds
 Cable Length:

Specification:

Description: std. rotary spring rtn std pretravel CW
 Body Style/Type Description: NEMA Square D 9007 Limit Switches 9007C Heavy Duty SemiModular 39mm Metal Body
 Head Type: 9007B rotary spring return, std. pretravel, CW
 Lever Arms: Lever Arm (ordered separately)
 Body with Contact Type: 1 N.O. / 1 N.C. SPDT Snap Action
 Conduit Thread: 0.5 NPT
 Ampere Rating Continuous: 10A
 Maximum Voltage Rating: 600V
 Actuation: CW
 Actuator Action: Spring Return - standard Pretravel
 Lever Arm Length:
 Roller Dimension:
 Roller Material:
 Contact Configuration: 1 N.O./1 N.C.
 Contact Operation: Snap Action
 Connection Type: Conduit Entrance (0.5 Inch NPT)
 Head Material: Zinc Alloy
 Positive Opening: No