



Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

9007CR53GD



Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Terminal Type: Screw Clamp
 Enclosure Rating: NEMA 1/2/4/6/6P/7/9/12/13
 Approvals: UL # E10054 CCN NOIV - CSA # LR26817 Class 3218-023
 Weight: 2.25 lb
 Conforming to Standards: NEMA and UL type 6P, NOM, ANCE
 RoHS: No
 Operating Temperature Range: 0 to 185 °F
 Shock Resistance: 60 gn (9ms)
 Vibration Resistance: 25 gn (10-150 Hz, 11 ms)
 Max. Actuation Speed :
 Repeat Accuracy: 0.03mm (0.001 in.)
 Operating Torque/Force: 4 Pounds
 Cable Length:

Specification:

Description: NEMA 7/9 metal side push rod plunger head, adj., spring rtn
 Body Style/Type Description: NEMA Square D 9007 Limit Switches 9007C Heavy Duty SemiModular 39mm Metal Body
 Head Type: 9007GD metal side push rod plunger head, Adjustable, spring return
 Lever Arms:
 Body with Contact Type: 1 N.O. / 1 N.C. SPDT Snap Action
 Conduit Thread: 0.5 NPT
 Ampere Rating Continuous: 10A
 Maximum Voltage Rating: 600V
 Actuation: Horizontal
 Actuator Action: Spring Return
 Lever Arm Length:
 Roller Dimension:
 Roller Material:
 Contact Configuration: 1 N.O./1 N.C.
 Contact Operation: Snap Action
 Connection Type: Conduit Entrance (0.5 Inch NPT)
 Head Material: Zinc Alloy
 Positive Opening: No