


Note:

- Drawings Not To Scale
- Drawings Subject to Change Without Notice
- Dimensions are inches next to [Millimeters]

Part No.:

9007FTUB12



Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Terminal Type: Screw Clamp
 Enclosure Rating: NEMA 1/2/4/12/13/IP65/IP66/IP67
 Approvals: UL # Number E78403 CCN NKCR - CSA # LR25490 Class 3211-03 - CE
 Weight: 2.57 lb. (1.17 kg)
 Conforming to Standards: NEMA A600 UL508
 RoHS: No
 Operating Temperature Range: -10 to 180° F
 Shock Resistance: 30G
 Vibration Resistance: 10G (10-150Hz)
 Max. Actuation Speed :
 Repeat Accuracy: ±0.004 in (0.10 mm)
 Operating Torque/Force: 8 in-Pounds
 Cable Length:

Specification:

Description: 9007FT, rotary, maintained CW&CCW, seq 12, style B, 0.5" NPT
 Body Style/Type Description: NEMA Square D Limit Switches 9007 T/FT Severe Duty 59mm Metal Body
 Head Type: Rotary lever operated
 Lever Arms: Ordered separately
 Body with Contact Type: Maintained CW&CCW, Sequence 12, Style B baseplate, 1/2-14 NPT
 Conduit Thread: 1/2-14 NPT
 Ampere Rating Continuous: 20A
 Maximum Voltage Rating: 600V
 Actuation: CW and CCW
 Actuator Action: Maintained
 Lever Arm Length:
 Roller Dimension:
 Roller Material:
 Contact Configuration: 1 N.O./1 N.C.
 Contact Operation: Snap Action
 Connection Type: Conduit Entrance (1/2-14 NPT)
 Head Material: Cast Zinc
 Positive Opening: No