


Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

9016GVG1J99



Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Fluid Characteristics: Hydraulic oil, noncorrosive liquids, air, noncorrosive gas
 Enclosure Rating: NEMA 1
 Certifications: UL Listed File: E12158 CCN NKPZ - CSA Certified File: LR25490
 RoHS: No
 Precision: +/- 1% of the adjustable range over 1,000,000 operations
 Ambient air temp. for operation: -10 to 185 °F (-23 to 85 °C)
 Vibration Resistance: 50 g
 Repeat Accuracy: 0.4% of the adjustable range
 Operating rate: ≤ 120 operating cycles per minute
 Weight: 4.6 lb

Specification:

Description: NEMA Square D Vacuum Switches, Power Rated Pressure Switches, 9016GVG
 Pressure Range: Cut-Out Range 5 - 25 (In. of Hg) / Cut-In Range 0 - 20 Hg (In of Hg)
 Max. Allowable Pressure: 150 psi
 Differential Type: Adjustable
 Output: DPST
 Electrical Connection: 1/2 - 14 NPT Conduit connection
 Differential: 5 to 10 in of Mercury
 Fluid Connection: 1/4in - 18 NPSF Pressure connection
 Actuator Type: diaphragm
 Rated Supply voltage: 480VAC
 Continuous Current Rating: