



## Main

|                              |   |
|------------------------------|---|
| Range of product             | Square D Pumptrol   |
| Product or component type    | Mechanical alternator   |
| Device application           | Closed tank with bushing                                      |
| Device short name            | 9038C   |
| Product specific application | Mechanically alternating the operation of two pumps or motors |
| Electrical circuit type      | Power circuit   |
| Quantity per set             | Set of 1  |
| Type of packing              | Individual  |

## Complementary

|                                 |  |
|---------------------------------|--|
| Product destination             | For closed tank  |
| Device mounting                 | Screw-in bushing   |
| Cable entry number              | 8 knock-outs for 1/2" or 3/4"conduit UL 508  |
| Contacts type and composition   | 4 NC, snap action, DPST-DB, Form YY  |
| Controlled fluid                | Fresh water specific gravity of 0.85 in or higher 0...220 °F (-18...104 °C)<br>Sea water specific gravity of 0.85 in or higher 0...220 °F (-18...104 °C)<br>Hydraulic oil specific gravity of 0.85 in or higher 0...220 °F (-18...104 °C)<br>Corrosive fluid specific gravity of 0.85 in or higher 0...220 °F (-18...104 °C) |
| Motor power kW                  | 1.5 KW (2 hp) at 115 V AC, 1 phase<br>2.2 KW (3 hp) at 115 V AC, 3 phases<br>2.2 KW (3 hp) at 230 V AC, 1 phase<br>3.7 KW 5 hp)230 V AC, 3 phase<br>0.75 KW 1 hp)460 V AC, 3 phase<br>0.75 KW 1 hp)475 V AC, 3 phase<br>0.18 KW 0.25 hp)32 V DC<br>0.37 KW 0.5 hp)115 V DC<br>0.37 kW 0.5 hp)230 V DC                        |
| Electrical connection           | Screw-clamp terminals, clamping capacity: 10 AWG   |
| Contact operation               | Contacts close on liquid rise  |
| Float movement                  | 4.75...9.25 in adjustable  |
| Float position                  | Left   |
| Float rod angle                 | 90° (offset)   |
| Short-circuit protection        | 20 A cartridge fuse gG   |
| Local signalling                | With external pointer  |
| Materials in contact with fluid | Cast iron<br>Yellow brass<br>Nitrile (Buna-N) or equivalent rubber<br>316 stainless steel<br>304 stainless steel   |
| Enclosure material              | Painted cold-rolled steel  |
| Operating position              | Vertical position only   |
| Electrical durability           | 100 cycles 60 cyc/mn   |
| Mechanical durability           | 300 cycles   |
| Terminal block type             | 8 terminals  |
| Maximum operating rate          | 60 cyc/mn  |
| [Ui] rated insulation voltage   | 575 V conforming to UL 508   |
| Net Weight                      | 6.2 lb(US) (2.81 kg)   |
| Terminals description ISO n°1   | Line-load-load-line  |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                      |                                |
|----------------------|--------------------------------|
| Factory modification | Two-level non-alternating unit |
| Kit composition      | Float switch<br>Float<br>Rod   |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | UL 508<br>CE                              |
| Ambient air temperature for operation | -22...220 °F (-30...104 °C)               |
| Ambient air temperature for storage   | -22...220 °F (-30...104 °C)               |
| NEMA degree of protection             | NEMA 1 conforming to UL 50                |
| Product certifications                | CSA file LR25490<br>UL listed file E12158 |

## Ordering and shipping details

|                       |   |
|-----------------------|---|
| Category              | 21601 - 9037,9038 COMMERCIAL FLOAT SWITCHES |
| Discount Schedule     | CP7G  |
| GTIN                  | 00785901711933                              |
| Nbr. of units in pkg. | 1   |
| Package weight(Lbs)   | 8.76 lb(US) (3.97 kg)                       |
| Returnability         | No  |
| Country of origin     | MX  |

## Packing Units

|                  |                      |
|------------------|----------------------|
| Package 1 Height | 9.50 in (24.130 cm)  |
| Package 1 width  | 10.90 in (27.686 cm) |
| Package 1 Length | 12.30 in (31.242 cm) |

## Offer Sustainability

|                           |   |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation          | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive         | Not applicable, out of EU RoHS legal scope  |
| Environmental Disclosure  | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile       | <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|